



## RGB+CCT 50W 4200lm RGB+CCT 50W LED floodlight - RF and WiFi control - IP65 FUTT02

Ref. FUTT02



### Product data

|                         |                                      |
|-------------------------|--------------------------------------|
| Opening angle (°)       | 160                                  |
| Certs                   | CE, ROHS                             |
| Energy efficiency class | A+ (2021)                            |
| Connectivity            | WIFI                                 |
| CRI                     | 80-85                                |
| Dimensions (mm) LxWxH   | 220x310x50                           |
| Dimmable                | Yes                                  |
| Driver                  | Internal                             |
| Efficiency (Lm/w)       | 84                                   |
| Power factor (cosφ)     | 0.9                                  |
| Frequency (Hz)          | 50 - 60                              |
| Frequency of Use        | Intensive                            |
| Projector Range         | RGB                                  |
| Guarantee               | According to legal warranty: 3 years |
| IP                      | IP65                                 |
| Kelvin (K)              | 6500, 2700                           |

|                     |                             |
|---------------------|-----------------------------|
| Lumens (Lm)         | 4200                        |
| Material            | Metal                       |
| Material diffuser   | Crystal                     |
| Assembly            | Surface                     |
| Orientable          | Yes                         |
| Weight (g)          | 1900                        |
| Power (W)           | 50                          |
| Temperature range   | -20°F ~ +40°F               |
| Sensor              | No                          |
| Nominal Voltage (V) | 86-265                      |
| Type of LED         | SMD 3030                    |
| Key                 | Warm white, Cold white, RGB |
| UGR                 | No                          |
| Outdoor Use         | If                          |
| Recommended Use     | Garden                      |
| Service life (h)    | 50000                       |

## Product variants

### Reference

### Attributes

FUTT02

