







## Outdoor RGB+CCT LED floodlight - 30W - RF/WiFi - IP65 - Mi-Light


## Ref. FUTT03

 $Smart\,RGB+CCT\,LED\,projector\,made\,of\,high-quality\,aluminum, with an\,IP65\,protection\,rating,\,suitable\,for\,outdoor\,use.\,With\,a\,power\,of\,30W,\,it\,offers\,a\,luminous\,flux\,of\,3300lm.\,Offers\,a\,variety\,of\,16\,million\,customizable\,colors,\,along\,with\,brightness\,and\,color\,temperature\,adjustments\,to\,suit\,various\,preferences\,and\,environments.\,Compatible\,with\,RF\,RGB+CCT\,remote\,controllers\,and\,remotes\,from\,MiBoxer\,/\,Mi-Light.$ 



## **Product data**

Opening angle (°)	160
Certs	CE, ROHS
Energy efficiency class	F
Connectivity	Wifi, RF
CRI	80-85
Dimensions (mm) LxWxH	167 x 226.5 x 40
Dimmable	Yes
Control distance	30 minutes
Efficiency (Lm/w)	110
Projector Range	RGB
Guarantee	According to legal warranty: 3 years
IP	IP65
IP Kelvin (K)	IP65 2700 - 6500
Kelvin (K)	2700 - 6500
Kelvin (K) Lumens (Lm)	2700 - 6500 3300
Kelvin (K) Lumens (Lm) Assembly	2700 - 6500 3300 Surface
Kelvin (K) Lumens (Lm) Assembly Orientable	2700 - 6500 3300 Surface Yes
Kelvin (K) Lumens (Lm) Assembly Orientable Power (W)	2700 - 6500 3300 Surface Yes 30
Kelvin (K) Lumens (Lm) Assembly Orientable Power (W) Temperature range	2700 - 6500 3300 Surface Yes 30 -20°F ~ +45°F
Kelvin (K) Lumens (Lm) Assembly Orientable Power (W) Temperature range Sensor	2700 - 6500 3300 Surface Yes 30 -20°F ~ +45°F No







Recommended Use Garden, Hotels, Fascias

**Product variants** 

Reference Attributes



FUTT03