






## Fumagalli CECI 160 CCT GX53 10W LED ground recessed spotlight 10W

Recessed ground beacon from the brand Fumagalli, made of impact-resistant resin and designed to withstand extreme weather conditions. Featuring a circular shape and front light emission, the high-resistance recessed light is walkable by vehicles up to 5000Kg. It includes a socket for a LED bulb GX53, which is replaceable. The set includes a 10W LED bulb GX53, CCT (3000;4000;6500). The IP67 protection rating makes the CECI 160 recessed beacon suitable for outdoor installation, resistant to rain, humidity, cold, dust, and dirt. \*\* LED Bulb GX53 10W included \*\* 1x GX53 10W 230V CCT Ø160x111mm IP67



## **Product data**

CapGX53CertsCE, ROHSEnergy efficiency classA+ (2021)CRI80-85Dimensions (mm) LxWxHØ160x111Cutting dimensions (mm)Ø147x111DimmableNoEfficiency (Lm/w)120Power factor (cos\$)0.5Frequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP67Kelvin (K)3000, 4000, 6500Lumens (Lm)1200Material diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10Temperature range-20°F ~ +40°F	Case color	Black (use), Gray (to use)
Energy efficiency classA+ (2021)CRI80-85Dimensions (mm) LxWxHØ160x111Cutting dimensions (mm)Ø147x111DimmableNoEfficiency (Lm/w)120Power factor (cosφ)0.5Frequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP67Kelvin (K)3000, 4000, 6500Lumens (Lm)1200MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	Сар	
CRI80-85Dimensions (mm) LxWxHØ160x111Cutting dimensions (mm)Ø147x111DimmableNoEfficiency (Lm/w)120Power factor (cosφ)0.5Frequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP67Kelvin (K)3000, 4000, 6500Lumens (Lm)1200MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	Certs	CE, ROHS
Dimensions (mm) LxWxHØ160x111Cutting dimensions (mm)Ø147x111DimmableNoEfficiency (Lm/w)120Power factor (cosφ)0.5Frequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP67Kelvin (K)3000, 4000, 6500Lumens (Lm)1200MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	Energy efficiency class	A+ (2021)
Cutting dimensions (mm)Ø147x111DimmableNoEfficiency (Lm/w)120Power factor (cos \$\phi)0.5Frequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP67Kelvin (K)3000, 4000, 6500Lumens (Lm)1200MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	CRI	80-85
DimmableNoEfficiency (Lm/w)120Power factor (cosφ)0.5Frequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP67Kelvin (K)3000, 4000, 6500Lumens (Lm)1200MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	Dimensions (mm) LxWxH	Ø160x111
Efficiency (Lm/w)120Power factor (cosφ)0.5Frequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP67Kelvin (K)3000, 4000, 6500Lumens (Lm)1200MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	Cutting dimensions (mm)	Ø147x111
Power factor (cosφ)0.5Frequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP67Kelvin (K)3000, 4000, 6500Lumens (Lm)1200MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	Dimmable	No
Frequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP67Kelvin (K)3000, 4000, 6500Lumens (Lm)1200MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	Efficiency (Lm/w)	120
Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP67Kelvin (K)3000, 4000, 6500Lumens (Lm)1200MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	Power factor (cosφ)	0.5
GuaranteeAccording to legal warranty: 3 yearsIPIP67Kelvin (K)3000, 4000, 6500Lumens (Lm)1200MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	Frequency (Hz)	50 - 60
IPIP67Kelvin (K)3000, 4000, 6500Lumens (Lm)1200MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	Frequency of Use	normal
Kelvin (K)3000, 4000, 6500Lumens (Lm)1200MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	Guarantee	According to legal warranty: 3 years
Lumens (Lm)1200MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	IP	IP67
MaterialResinMaterial diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	Kelvin (K)	3000, 4000, 6500
Material diffuserPolycarbonateAssemblyRecessedOrientableNoPower (W)10	Lumens (Lm)	1200
Assembly Recessed Orientable No Power (W) 10	Material	Resin
OrientableNoPower (W)10	Material diffuser	Polycarbonate
Power (W) 10	Assembly	Recessed
	Orientable	No
Temperature range -20°F ~ +40°F	Power (W)	10
	Temperature range	-20°F ~ +40°F





B·			
BARC	ELOI	NA LEC	<b>)</b>

Nominal Voltage (V)	230
Type of LED	SMD 2835
Кеу	CCT
Outdoor Use	lf
Recommended Use	Garden
Service life (h)	25,000

## Product variants

Reference

Attributes

3F1.000.000.AXD1K

Case color : Black (use)

3F1.000.000.LXD1K

Case color : Gray (to use)