

CCT FUMAGALLI CECI 90 GU10 3.5W recessed LED ground beacon CCT FUMAGALLI CECI 90 GU10 3.5W


Ref. 1F1.000.000.AXU1K

Fumagalli Recessed Ground Light emits light in a circular shape, with a frosted diffuser. Made from high-resistance resin, it is walkable and can support loads up to 5000KG. It features a socket for a GU10 LED bulb. Includes a GU10 LED bulb of 3.5W, with a CCT system and a luminous intensity of 350lm. Adjustable CCT color temperature, allows you to set the temperature to 2700°K or 4000°. Using the switch directly on the bulb. 3.5W CCT GU10 Ø 92x127mm IP67

The same of the same of the same of		GU10 LED - CCT SETTABLE	
	THE COST	POWER	3,5 W
	B a	LUMINOUS FLUX	350 lm
2.5 W 2500 Im		SIZE & SOCKET	OU10 S
		EFFICIENCY	100 lm/W
	No.	VOLTAGE	100-240 V
	100	FREQUENCY	50/60 Hz
CCT SETTABLE	1500	CURRENT	70 mA
2700 K 6000 K		COLOR RENDERING INDEX RA	> 80
minimum land		SDCM	< 6
INDOR & OUTDOOR USE -30-69°C SAMERY VOLLEG SURGE RESISTANT		BEAM ANOLE	36*
	₹ (€	WARM UP TIME	< 0,5"
	СВ	SWITCHING CYCLE	> 25.000
		LIFETIME	25.000 h
	LVD EMC ERP	KELVIN SETTABLE	2700 K / 4000 K
	800m	REF. CODE	H.LED.GU10.CCT
	SG PSE-16-022000A1	COMPARISON	3,5W = 50W 400 Lm halogen

Product data

Light temperature	ССТ	
Сар	GU10	
Certs	CE, ROHS	
Energy efficiency class	A+ (2021)	
Dimensions (mm) LxWxH	Ø92x127	
Cutting dimensions (mm)	Ø85x127	
Dimmable	No	
Frequency (Hz)	50 - 60	
Frequency of Use	Intensive	
Guarantee	According to legal warranty: 3 years	
IP	IP67	
Kelvin (K)	4000, 2700	
Lumens (Lm)	350, 400	
Material	Resin	
Assembly	Recessed	
Power (W)	3.5	
Temperature range	-20°F ~ +40°F	
Nominal Voltage (V)	100-240	
Key	Warm white, Neutral white	
Outdoor Use	If	
Recommended Use	Garden	
Service life (h)	25,000	





Product variants

Reference Attributes



1F1.000.000.AXU1K Light temperature : CCT