



RGB LED floodlight 30W IP65 with 24-key remote control and stake

Ref. B1455-N

RGB LED Outdoor Projector with IP65 protection rating. Equipped with independent SMD2835 LED chips for red, green, and blue, featuring high brightness and intensity. Instant start, no flickering. Includes a 24-key IR remote control for color selection and effects such as flash, strobe, fade, and smooth color transitions. Comes with a 150cm long cable with a plug for standard Schuko base. Features memory effect: the projector will retain the color setting it had during the previous use. ** Includes plastic stake for driving into the ground** The RGB outdoor LED projector is commonly used for lighting parks and gardens, facades, walls, doors, commercial premises, pergolas, etc. 30W RGB 230V SMD2835 IP65 ¿Eres Profesional? ¡Regístrate y obtén tu descuento! [1] [1] /registro-profesionales

Product data

| | |
|-------------------------|------------|
| Light temperature | RGB (use) |
| Opening angle (°) | 120 |
| Certs | CE, ROHS |
| Energy efficiency class | A+ (2021) |
| Dimensions (mm) LxWxH | 138x147x40 |
| Dimmable | Yes |
| Driver | Internal |
| Power factor (cosφ) | 0.5 |
| Frequency (Hz) | 50 - 60 |

| | |
|---------------------|--------------------------------------|
| Frequency of Use | normal |
| Projector Range | RGB |
| Guarantee | According to legal warranty: 3 years |
| IP | IP65 |
| Material | Aluminum |
| Material diffuser | Crystal |
| Assembly | Surface |
| Orientable | Yes |
| Power (W) | 30 |
| Temperature range | -18°F ~ +55°F |
| Sensor | No |
| Nominal Voltage (V) | 230 |
| Type of LED | SMD 2835 |
| Key | RGB |
| UGR | No |
| Outdoor Use | If |
| Recommended Use | Garden |
| Service life (h) | 25,000 |

Product variants

Reference

Attributes

B1455-N

Light temperature : RGB (use)

