







Asymmetric LED floodlight 200W - 150lm/W - IP65

Ref. B8221

Asymmetrical LED projector industrial high performance, with a power of 200W and an efficiency of 150lm/W. Its asymmetric lens optimizes light distribution, making it ideal for sports facilities, industrial halls, workshops, or parking lots, among others. Available in cool white (5000K). **7 Year Warranty**



Product data

Beam angle (°)	80/150
Certs	CE, ROHS
Energy efficiency class	D
CRI	80-85
Dimensions (mm) LxWxH	438x396x60
Dimmable	No
Driver	Internal
Efficiency (Lm/w)	150
Power factor (cosφ)	0.9
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Projector Range	Asymmetrical
Warranty	7 years
IP	IP66
Kelvin (K)	5000
Lumens (Lm)	30000
Material	Aluminum
Material diffuser	Polycarbonate
Orientable	Yes
Power (W)	200
Sensor	No
Nominal Voltage (V)	100-240V

Better Heat Dissipation

Multi-board convection cooling design





Type of LED	Chip EPISTAR
Key	Cold white
Outdoor Use	Yes
Recommended Use	Garden, Industrial Warehouses
Service life (h)	50000
Service life (h)	50000

Product variants

Reference Attributes



B8221