

## Square recessed LED downlight plate with adjustable diameter 20W

Recessed LED Downlight 20W adjustable for variable drill sizes from 50mm to 205mm. The adjustable LED downlight is perfect for installation in both round and square holes, as the wings adapt to the size, pressing the LED downlight against the ceiling. For home use, with an average luminous flux of 1800 lumens. Power 20W 230x230mm 1800 Lumens Adjustable IP20


### Product data

Light temperature	4000°K, 6000K
Opening angle (°)	160
Certs	CE, ROHS
Energy efficiency class	F
CRI	80-85
Dimensions (mm) LxWxH	230x230x11
Cutting dimensions (mm)	Ø50-205
Dimmable	No
Efficiency (Lm/w)	90
Form	Ultrafine, Cuadrado
Frequency (Hz)	50 - 60
Frequency of Use	normal
Guarantee	3 years
IP	IP20
Kelvin (K)	4000, 6000
Lumens (Lm)	1700
Material	Aluminum
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	No
Temperature range	-20°F ~ +40°F
Nominal Voltage (V)	230V AC



Type of LED	SMD 2835
Key	Cold white, Neutral white
Outdoor Use	No
Service life (h)	25,000

Product variants

Reference	Attributes	
B1275-7-BF	Light temperature : 6000K	
B1275-7-BN	Light temperature : 4000°K	