



Recessed circular LED downlight - 25W - Professional use - Ø190 mm

Downlight LED empotrable de 25W, diseño circular en aluminio, ideal para uso intensivo. Ofrece 2500 lúmenes y alta eficiencia de 100lm/W, perfecto para entornos profesionales. Disponible en blanco cálido (3000K), blanco neutro (4000K) y blanco frío (6000K).



Product data

Light temperature	3000°K, 4000°K, 6500K
Beam angle (°)	100
Certs	CE, ROHS
Energy efficiency class	F
CRI	80-85
Dimensions (mm) LxWxH	Ø230x35
Cutting dimensions (mm)	Ø187
Dimmable	No
Efficiency (Lm/w)	114
Power factor (cosφ)	0.98
Form	Circular, Ultrafine
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Warranty	3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000

Material	Aluminum
Assembly	Recessed
Orientable	No
Power (W)	25
Temperature range	-20°F ~ +40°F
Sensor	No
Nominal Voltage (V)	230V AC
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white
Outdoor Use	No
Service life (h)	25,000

Product variants

Reference

Attributes

B1264BC

Light temperature : 3000°K



B1264BF

Light temperature : 6500K



B1264BN

Light temperature : 4000°K

