





Linkable LED tri-proof slim batten light - 150cm - 45W - 4500lm - IP65

Ref. B8410-2-150BF

Compact design, low consumption, and high luminous performance (100 lm/W) linked slim LED waterproof screen. It has a length of 150cm and a power of 45W. Thanks to its waterproof, dustproof, and external agent-resistant design (IP65), it is perfect for humid and outdoor environments. Due to its high-quality materials, durability, and its lighting in cool white tone (6500 K), it is especially recommended for farms and breeding facilities. Protect your investment with this waterproof LED screen!



Product data

Light temperature	6500K
Opening angle (°)	140
Certs	CE, ROHS
Energy efficiency class	F
CRI	80-85
Dimensions (mm) LxWxH	1570 X 50 X 34
Dimmable	No
Driver	Internal
Efficiency (Lm/w)	100
Power factor (cosφ)	0.9
[maguapay/1]=\	FO (0
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Frequency of Use	Intensive
Frequency of Use Guarantee	Intensive According to legal warranty: 3 years
Frequency of Use Guarantee IP	Intensive According to legal warranty: 3 years IP65
Frequency of Use Guarantee IP Kelvin (K)	According to legal warranty: 3 years IP65 6500
Frequency of Use Guarantee IP Kelvin (K) Lumens (Lm)	Intensive According to legal warranty: 3 years IP65 6500 4500
Frequency of Use Guarantee IP Kelvin (K) Lumens (Lm) Material	Intensive According to legal warranty: 3 years IP65 6500 4500 Plastic
Frequency of Use Guarantee IP Kelvin (K) Lumens (Lm) Material Material diffuser	Intensive According to legal warranty: 3 years IP65 6500 4500 Plastic Polycarbonate
Frequency of Use Guarantee IP Kelvin (K) Lumens (Lm) Material Material diffuser Assembly	Intensive According to legal warranty: 3 years IP65 6500 4500 Plastic Polycarbonate Surface





Sensor	No
Nominal Voltage (V)	220 - 240 V AC
Type of LED	SMD 2835
Key	Cold white
Outdoor Use	If
Recommended Use	Commerce, Industry, Parking
Service life (h)	25,000

Product variants

Reference Attributes



B8410-2-150BF Light temperature : 6500K