



## Recessed LED spotlight "KOPPA"- 6W - 15° Optics - Cutout Ø 65mm - Low UGR

6W recessed LED spotlight with anti-glare technology that ensures maximum visual comfort. Made with top-quality components, it features a LIFUD driver and a Cree LED chip that provides powerful and defined lighting at a 15° angle. Available in black and white and in two color temperatures: warm white and neutral white.



### Product data

|                         |                                      |
|-------------------------|--------------------------------------|
| Housing color           | White, Black                         |
| Light temperature       | 2700°K, 4000°K                       |
| Opening angle (°)       | 15°                                  |
| Certs                   | CE, ROHS                             |
| CRI                     | 80-85                                |
| Dimensions (mm) LxWxH   | Ø 70 x 77                            |
| Cutting dimensions (mm) | Ø 65                                 |
| Dimmable                | No                                   |
| Driver                  | Lifud                                |
| Form                    | Circular                             |
| Guarantee               | According to legal warranty: 3 years |
| IP                      | IP20                                 |
| Kelvin (K)              | 4000, 2700                           |
| Lumens (Lm)             | 500                                  |
| Material                | Aluminum, Plastic                    |
| Assembly                | Recessed                             |
| Orientable              | No                                   |
| Power (W)               | 6                                    |
| Nominal Voltage (V)     | 220 - 240 V AC                       |
| Type of LED             | COB                                  |
| Key                     | Warm white, Neutral white            |
| UGR                     | UGR19                                |

Ø65mm



Outdoor Use

No

Product variants

| Reference       | Attributes                                       |   |
|-----------------|--|---|
| MODR6-15-B-2700 | Housing color: White, Light temperature : 2700°K |    |
| MODR6-15-B-4000 | Housing color: White, Light temperature : 4000°K |    |
| MODR6-15-N-2700 | Housing color: Black, Light temperature : 2700°K |   |
| MODR6-15-N-4000 | Housing color: Black, Light temperature : 4000°K |  |