



## High power CCT LED linear luminaire - 40W - 120cm

## Ref. B8596-CCT-120

120 cm LED linear luminaire with 40W power, especially useful for replacing traditional fluorescent tubes, achieving a great energy savings. Provides high-quality lighting, without flicker, with a luminous efficiency of 120lm/W and a CRI>80. It incorporates a CCT selector, which allows you to change the color temperature between three different shades: warm white (3000K), neutral white (4000K), and cool white (6000K). \*\*Includes: screws and a set of metal staples for fastening\*\*



## Product data

Light temperature	ССТ
Opening angle (°)	120
Certs	CE, ROHS
Energy efficiency class	E
CRI	80-85
Dimensions (mm) LxWxH	1200 x 62 x 64
Dimmable	No
Efficiency (Lm/w)	100
Power factor (cosφ)	0.9
Frequency (Hz)	50 - 60
Frequency of Use	normal
Trequency of 050	
Guarantee	According to legal warranty: 3 years
	According to legal warranty: 3 years
Guarantee	
Guarantee IP	IP20
Guarantee IP Kelvin (K)	IP20 3000, 4000, 6000
Guarantee IP Kelvin (K) Lumens (Lm)	IP20 3000, 4000, 6000 4800
Guarantee IP Kelvin (K) Lumens (Lm) Material	IP20 3000, 4000, 6000 4800 Metal
Guarantee IP Kelvin (K) Lumens (Lm) Material Material diffuser	IP20 3000, 4000, 6000 4800 Metal Polycarbonate
Guarantee IP Kelvin (K) Lumens (Lm) Material Material diffuser Power (W)	IP20 3000, 4000, 6000 4800 Metal Polycarbonate 40
Guarantee IP Kelvin (K) Lumens (Lm) Material Material diffuser Power (W) Temperature range	IP20 3000, 4000, 6000 4800 Metal Polycarbonate 40 -20°F ~ +40°F
Guarantee IP Kelvin (K) Lumens (Lm) Material Material diffuser Power (W) Temperature range Sensor	IP20 3000, 4000, 6000 4800 Metal Polycarbonate 40 -20°F ~ +40°F No





Кеу	Warm white, Cold white, Neutral w	hite	
UGR		No	
Outdoor Use		No	
Service life (h)	25,	000	
Product variants			
Reference	Attributes		
B8596-CCT-120	Light temperature : CCT		