





 $\mathsf{CCT}$ 

Metal

No

Polycarbonate

-20°F ~ +40°F

220 - 240 V AC

SMD 2835



## High power CCT LED linear luminaire - 40W - 120cm

## Ref. B8596-CCT-120


**Product data** 

Light temperature

 $120\,cm\,LED\,linear\,luminaire\,with\,40W\,power, especially\,useful\,for\,replacing\,traditional\,fluorescent\,tubes,\\ achieving\,a\,great\,energy\,savings.\,Provides\,high-quality\,lighting,\,without\,flicker,\,with\,a\,luminous\,efficiency\,of\\ 120lm/W\,\,and\,a\,CRI>80.\,It\,incorporates\,a\,CCT\,selector,\,which\,allows\,you\,to\,change\,the\,color\,temperature\,between\,three\,different\,shades:\,warm\,white\,(3000K),\,neutral\,white\,(4000K),\,and\,cool\,white\,(6000K).\,^{**}Includes:\,screws\,and\,a\,set\,of\,metal\,staples\,for\,fastening^{**}$ 



Beam angle (°)	120
Certs	CE, ROHS
Energy efficiency class	E
CRI	80-85
Dimensions (mm) LxWxH	1200 x 62 x 64
Dimmable	No
Efficiency (Lm/w)	100
Power factor (cosφ)	0.9
Frequency (Hz)	50 - 60
Frequency of Use	normal
Warranty	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	4800



Type of LED

Material

Power (W)

Sensor

Material diffuser

Temperature range

Nominal Voltage (V)



Key	Warm white, Cold white, Neutral white
UGR	No
Outdoor Use	No
Service life (h)	25,000

## **Product variants**

Reference Attributes

B8596-CCT-120 Light temperature : CCT