



Support Common LED Driver ICs on the Market

WS2811	SM16703	TM1814	WS2815
WS2812B	TM1804	TM1913	WS2818
WS2813	UCS1903	P9813	P943S
WS2801	LPD6803	INK1003	P9411
SK6812	LPD6806	DMA512	P9413
SK6812-RGBW	APA102	APA105	TX1812
TX1813	GS8206	GS8208	SK6822
P9414	P9412		

It can support WS2812B and WS2813. But there is no options on setting page.
Please choose WS2811 if connect it to WS2812B and WS2813.
It can't support 5050 ordinary RGB LED strips with no ICs.

Controlador LED IC pixel WIFI RGB/RGBW - 5-24V DC - 2048 pixeles

Ref. SP108E

El controlador LED IC está diseñado para controlar tiras LED IC RGB/RGBW de forma remota desde el teléfono móvil. Cuenta con una tensión de entrada desde 5 a 24V DC y puede controlar hasta 2048 píxeles. Es posible seleccionar cualquier efecto o escena a partir de 180 patrones multicolor preestablecidos y 8 patrones monocolor. También permite crear patrones propios a partir de imágenes. El brillo y la velocidad son ajustables. Se controla fácilmente por WiFi a través de una aplicación que se debe descargar en el móvil.



Datos del producto

Certificados	CE, ROHS
Clase eficiencia energética	A+ (2021)
Conectividad	Wifi
Garantía	3 años
IP	IP20
Material	Plástico
Rango detección (m)	30
Rango temperatura	-20°C ~ +40°C
Tensión Nominal (V)	5-24V
Tonalidad	RGB
Uso Exterior	No



Variantes de producto

Referencia

Atributos

SP108E

