



Support Common LED Driver ICs on the Market



WS2811	SM16703	TM1814	WS2815
WS2812B	TM1804	TM1913	WS2818
WS2813	UCS1903	P9813	P943S
WS2801	LPD6803	INK1003	P9411
SK6812	LPD6806	DMA512	P9413
SK6812-RGBW	APA102	APA105	TX1812
TX1813	GS8206	GS8208	SK6822
P9414	P9412		

It can support WS2812B and WS2813. But there is no options on setting page.
Please choose WS2811 if connect it to WS2812B and WS2813.
It can't support 5050 ordinary RGB LED strips with no ICs.

Contrôleur LED IC pixel WIFI RGB/RGBW - 5-24V DC - 2048 pixels

Ref. SP108E

Le contrôleur LED IC est conçu pour contrôler à distance des bandes LED RGB/RGBW depuis un téléphone mobile. Il a une tension d'entrée allant de 5 à 24V CC et peut contrôler jusqu'à 2048 pixels. Il est possible de sélectionner n'importe quel effet ou scène parmi 180 motifs multicolores prédéfinis et 8 motifs monochromes. Il permet également de créer des motifs personnalisés à partir d'images. La luminosité et la vitesse sont réglables. Il est facilement contrôlé via WiFi à l'aide d'une application qui doit être téléchargée sur l'appareil mobile.



Caractéristiques du produit

Certificats	CE, ROHS
Classe d'efficacité énergétique	A+ (2021)
Connectivité	Wifi
Garantie	3 ans
IP	IP20
Matériau	Plastique
Plage de détection (m)	30
Plage de température	-20°C ~ +40°C
Tension Nominale (V)	5-24V
Tonalité	RVB
Usage extérieur	Non



Variantes du produit

Référence

Attributs

SP108E

