



## Pack of 8 slim LED panels 60X60 cm - Driver Philips - 44W - UGR19

PACK x 8 recessed LED panels 60X60 cm - Philips Driver. Elegant and ultra-slim panels with advanced technology for powerful and even lighting in three shades of white (3000K, 4000K, 6000K). They have a power of 44W and a luminous flux of 3800 lumens. Ideal for offices, conference rooms, schools, or hospitals. High color rendering index (CRI>80) for accurate color reproduction and low glare index (UGR≤19). They can be mounted on false ceilings or embedded in plasterboard with a recessed frame (not included).



## Product data

| Light temperatureCold White (DO NOT USE), Warm White ( | DO NOT USE), Neutral White (DO NOT USE) |
|--|---|
| Certs  | CE, ROHS                                |
| Energy efficiency class                                | A+ (2021)                               |
| CRI  | 80-85                                   |
| LED Panel Dimensions                                   | 60x60                                   |
| Driver   | Philips                                 |
| Frequency (Hz)   | 50 - 60                                 |
| Frequency of Use                                       | Intensive                               |
| Guarantee  | According to legal warranty: 3 years    |
| IP   | IP20                                    |
| Kelvin (K)   | 3000, 4000, 6000                        |
| Lumens (Lm)  | 3800                                    |
| Assembly   | Recessed                                |
| Orientable   | No                                      |
| Power (W)  | 44                                      |
| Sensor   | No                                      |
| Type of LED  | SMD 2835                                |
| Key  | Warm white, Cold white, Neutral white   |
| UGR  | UGR19                                   |
| Outdoor Use  | No                                      |
| Service life (h)                                       | 25,000                                  |
|  |   |





## Reference Attributes K5235-BC-8 Light temperature : Warm White (DO NOT USE) K5235-BF-8 Light temperature : Cold White (DO NOT USE)

Light temperature : Neutral White (DO NOT USE)

K5235-BN-8