



Pack of 12 slim LED panels 120X30 cm - Driver Philips - 44W - UGR19

PACK x 12 recessed LED panels 120x30cm - PHILIPS driver. The panels feature a sleek, ultra-thin design and cutting-edge technology that allows them to provide powerful, even lighting in 3 color temperatures: warm white (3000K), neutral white (4000K), and cool white (6000K). They incorporate a micro-prismatic diffuser that ensures glare-free lighting (UGR<19), ideal for offices, conference rooms, schools, or hospitals. Thanks to their high color rendering index (CRI>80), they reproduce colors very similar to natural light. The panels can be mounted on false ceilings (removable ceiling tiles of 120x30cm) or directly embedded in drywall using an embedding frame (not included).



Product data

Light temperatureCold White (DO NOT USE) , Warm White (DO NOT USE) , Neutral White (DO NOT USE)

| | |
|-----------------------|---------------------------------------|
| Certs | CE, ROHS |
| CRI | 80-85 |
| Dimensions (mm) LxWxH | 1200 x 300 x 6 |
| LED Panel Dimensions | 120x30 |
| Dimmable | Optional, replacing the driver |
| Driver | Philips |
| Frequency (Hz) | 50 - 60 |
| Frequency of Use | Intensive |
| Guarantee | According to legal warranty: 3 years |
| IP | IP20 |
| Kelvin (K) | 3000, 4000, 6000 |
| Lumens (Lm) | 2900 |
| Material diffuser | Polycarbonate |
| Assembly | Recessed |
| Power (W) | 44 |
| Sensor | No |
| Nominal Voltage (V) | 220 - 240 V AC |
| Type of LED | SMD 2835 |
| Key | Warm white, Cold white, Neutral white |
| UGR | UGR19 |
| Outdoor Use | No |
| Service life (h) | 25,000 |



Product variants

| Reference | Attributes | |
|-------------|--|---|
| K5236-BC-12 | Light temperature : Warm White (DO NOT USE) |  |
| K5236-BF-12 | Light temperature : Cold White (DO NOT USE) |  |
| K5236-BN-12 | Light temperature : Neutral White (DO NOT USE) |  |