


Pack of 12 slim LED panels 120X30 cm - Driver Philips - 44W - UGR19

PACK x 12 recessed LED panels 120x30cm - PHILIPS driver. The panels feature a sleek, ultra-thin design and cutting-edge technology that allows them to provide powerful, even lighting in 3 color temperatures: warm white (3000K), neutral white (4000K), and cool white (6000K). They incorporate a micro-prismatic diffuser that ensures glare-free lighting (UGR<19), ideal for offices, conference rooms, schools, or hospitals. Thanks to their high color rendering index (CRI>80), they reproduce colors very similar to natural light. The panels can be mounted on false ceilings (removable ceiling tiles of 120x30cm) or directly embedded in drywall using an embedding frame (not included).



Product data

Light temperature	Cold White , Warm White , Neutral White
Certs	CE, ROHS
CRI	80-85
Dimensions (mm) LxWxH	1200 x 300 x 6
LED Panel Dimensions	120x30
Dimmable	Optional, replacing the driver
Driver	Philips
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Warranty	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	2900
Material diffuser	Polycarbonate
Assembly	Recessed
Power (W)	44
Sensor	No
Nominal Voltage (V)	220 - 240 V AC
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white
UGR	UGR19
Outdoor Use	No



Service life (h) 25,000

Product variants

Reference	Attributes	
K5236-BC-12	Light temperature : Warm White	
K5236-BF-12	Light temperature : Cold White	
K5236-BN-12	Light temperature : Neutral White	