



Pack of 2 slim LED panels 120X60cm - PHILIPS Driver - 72W - UGR19

PACK x 2 recessed LED panels 120x60cm - PHILIPS driver. The panels feature a sleek, ultra-slim design and cutting-edge technology that allows them to provide powerful, uniform lighting in 3 shades: warm white (3000K), neutral white (4000K), and cool white (6000K). They are high-efficiency fixtures that have a power of 72W and a luminous flux of 5900 lumens. They incorporate a micro-prismatic diffuser that ensures glare-free lighting (UGR≤19), ideal for offices, conference rooms, schools, or hospitals. Thanks to their high color reproduction index (CRI>80), they reproduce colors very similarly to natural light. The panels can be mounted in false ceilings or directly embedded in plasterboard using a recessed frame (not included).



Product data

Light temperatureCold White (Wahn White) (Kearlan WhiteOpening angle (°)160CertsCE, ROHSEnergy efficiency classA+ (2021)CRI80-85LED Panel Dimensions120x60DriverPhilipsFrequency (Hz)50 - 60Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral whiteUGRUGR19	Light temperature	Cold White , Warm White , Neutral White
CertsCE, ROHSEnergy efficiency classA+ (2021)CRI80-85LED Panel Dimensions120x60DriverPhilipsFrequency (Hz)50 - 60Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	o	
CRI80-85LED Panel Dimensions120x60DriverPhilipsFrequency (Hz)50 - 60Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white		
CRI80-85LED Panel Dimensions120x60DriverPhilipsFrequency (Hz)50 - 60Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	Energy efficiency class	A+ (2021)
DriverPhilipsFrequency (Hz)50 - 60Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white		80-85
Frequency (Hz)50 - 60Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	LED Panel Dimensions	120x60
Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	Driver	Philips
GuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	Frequency (Hz)	50 - 60
IPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	Frequency of Use	Intensive
Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	Guarantee	According to legal warranty: 3 years
Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	IP	IP20
AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	Kelvin (K)	3000, 4000, 6000
OrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	Lumens (Lm)	5900
Power (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	Assembly	Recessed
Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	Orientable	No
SensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	Power (W)	72
Nominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	Temperature range	-18°F ~ +55°F
Type of LED SMD 4014 Key Warm white, Cold white, Neutral white	Sensor	No
Key Warm white, Cold white, Neutral white	Nominal Voltage (V)	220 - 240 V AC
	Type of LED	SMD 4014
UGR UGR19	Кеу	Warm white, Cold white, Neutral white
	UGR	UGR19





Outdoor Use	No	
Recommended Use	Hotels, Offices, Commerce, Parking	
Service life (h)	25,000	
Product variants		
Reference	Attributes	
K5234-BF-2	Light temperature : Cold White	Parts Parts Control
K5234-BN-2	Light temperature : Neutral White	