



## Slim surface LED panel 60x60cm - OSRAM Driver - 40W - UGR18 - CRI90 - With mounting KIT

## Ref. B4292-UGR18-BN

The surface LED panel with OSRAM driver features a sleek, ultra-thin design and cutting-edge technology that allows it to provide powerful, uniform lighting in neutral white tones (4000K). It is a high-efficiency luminaire with a power of 40W and a luminous flux of 4000 lumens. It incorporates a micro-prismatic diffuser that ensures glarefree lighting (UGR=18), ideal for offices, conference rooms, schools, or hospitals. Thanks to its high color rendering index (CRI>90), it reproduces colors very similarly to natural light. Includes surface mount kit with all the accessories for simple and quick installation.



$\Box$		_1		-4	L _	١ _	ta	
$\nu$	ro	п	11	$c_1$		П	$T \cap$	
	$I \cup I$	и	и	v	. и	м	LUI	

Certs	CE, ROHS
Energy efficiency class	A+ (2021)
CRI	90-95
Dimensions (mm) LxWxH	23.4x23.4x0.37
LED Panel Dimensions	60x60
Dimmable	Optional, replacing the driver
Driver	External
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	4000
Lumens (Lm)	4000
Material diffuser	Polycarbonate
Assembly	Surface
Orientable	No
Power (W)	40
Temperature range	-0°F ~ +30°F
Sensor	No
Nominal Voltage (V)	220 - 240 V AC
Key	Neutral white
UGR	UGR18







Outdoor UseNoRecommended UseKitchensService life (h)30000

## **Product variants**

Reference Attributes



B4292-UGR18-BN