








LED Strip 220V - 300W (2400xSMD2835) -12mm - Outdoor use: IP67 - 20 meter roll

220V LED strip suitable for outdoor use in a 20-meter roll. It connects directly to the electrical current without the need for a transformer or rectifier. Incorporates high-quality SMD2835 LED chips with a density of 120 $chips/meter, which provide a total power of 300W. It has the possibility to make cuts every 10 \, cm, making it very 10 \, cm,$ $versatile \ for \ different \ lighting \ projects. \ lts \ great \ flexibility \ allows \ it \ to \ adapt \ to \ almost \ any \ surface \ and \ it \ is \ also$ suitable for outdoor use thanks to its high level of protection: IP67, which protects it from external factors such as $rain, dust, or\ moisture.\ It\ has\ a\ beam\ angle\ of\ 180°\ and\ a\ high\ color\ rendering\ index\ (CRI>90), which\ allows\ it\ to$ reproduce colors faithfully, similar to natural light. Available in warm white (2700K), neutral white (4000K), and $cool\ white\ (6000K).\ Due\ to\ its\ characteristics, it\ is\ ideal\ for\ installation\ in\ places\ where\ high\ brightness\ is\ required.$



Pr		_1		-4	_1	_	4 -	
P^{r}	'n	п	11	c_{T}	п	п	TA	
	\mathbf{v}	ч	и	UL.	м	ч	LUI	

Light temperature	2700°K (use), 4000°K (use), 6000K (use)
Adhesive	3M
Opening angle (°)	180
Certs	CE, ROHS
CRI	90-95
Efficiency (Lm/w)	96
Frequency (Hz)	50 - 60
Frequency of Use	normal
Guarantee	According to legal warranty: 3 years
IP	IP67
Kelvin (K)	4000, 6000, 2700
Lumens (Lm)	32600, 35720
# Chips per meter	120
Power (W)	380
Power/m (W/m)	19
Temperature range	-20°F ~ +40°F
Nominal Voltage (V)	220 - 240 V AC
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white
Outdoor Use	If





Product variants

Reference Attributes



%-10 cm





NO NECESITA RECTIFICADOR

%-10 cm

B1540-270

Light temperature : 2700°K (use)

B1540-BF

B1540-BN

Light temperature : 6000K (use)

Light temperature : 4000°K (use)

2 of 2