





Fixed LED GOBO projector - 10W - Indoor - 20° Optics - IP20

Fixed LED GOBO Projector with 10W power for projecting logos, images, and badges indoors. Logo projectors are also known as LED GOBO, GOBO projector, or GOBO LED. Projects static images in high definition. Indoor use (IP20). 20° Optics with manually adjustable focus. It reaches a range of 2-3 meters in darkness and 1-2 meters in daylight, with a light intensity of 1000 lumens. Barcelona LED offers laser engraving service for logos on mirror glass. The purchase of the projector includes the engraving of a first logo up to 4 colors for free (estimated delivery time: 10-15 days).



Product data

CertsCE, ROHSEnergy efficiency classA+ (2021)CRI80-85Dimensions (mm) LxWxH275x120x80DimmableNoDriverInternalFrequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)6000Lumens (Lm)1000MaterialMetalMaterial diffuserCrystalAssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo	Case color	Black (use)	
Energy efficiency classA+ (2021)CRI80-85Dimensions (mm) LxWxH275x120x80DimmableNoDriverInternalFrequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)6000Lumens (Lm)1000MaterialMetalMaterial diffuserCrystalAssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo			
CRI80-85Dimensions (mm) LxWxH275x120x80DimmableNoDriverInternalFrequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)6000Lumens (Lm)1000MaterialMetalMaterial diffuserCrystalAssemblySurfaceTemperature range-18°F ~+55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo			
Dimensions (mm) LxWxH275x120x80DimmableNoDriverInternalFrequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)6000Lumens (Lm)1000MaterialMetalMaterial diffuserCrystalAssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo			
DimmableNoDriverInternalFrequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)6000Lumens (Lm)1000MaterialMetalMaterial diffuserCrystalAssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo			
DriverInternalFrequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)6000Lumens (Lm)1000MaterialMetalMaterial diffuserCrystalAssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo		275x120x80	
Frequency (Hz)50 - 60Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)6000Lumens (Lm)1000MaterialMetalMaterial diffuserCrystalAssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo	Dimmable	No	
Frequency of UsenormalGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)6000Lumens (Lm)1000MaterialMetalMaterial diffuserCrystalAssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo	Driver	Internal	
GuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)6000Lumens (Lm)1000MaterialMetalMaterial diffuserCrystalAssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo	Frequency (Hz)	50 - 60	
IPIP20Kelvin (K)6000Lumens (Lm)1000MaterialMetalMaterial diffuserCrystalAssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo	Frequency of Use	normal	
Kelvin (K)6000Lumens (Lm)1000MaterialMetalMaterial diffuserCrystalAssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo	Guarantee	According to legal warranty: 3 years	
Lumens (Lm)1000MaterialMetalMaterial diffuserCrystalAssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo	IP	IP20	
MaterialMetalMaterial diffuserCrystalAssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo	Kelvin (K)	6000	
Material diffuserCrystalAssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo	Lumens (Lm)	1000	
AssemblySurfaceTemperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo	Material	Metal	
Temperature range-18°F ~ +55°FNominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo	Material diffuser	Crystal	
Nominal Voltage (V)220 - 240 V ACType of LEDCOBKeyCold whiteUGRNo	Assembly	Surface	
Type of LED COB Key Cold white UGR No	Temperature range	-18°F ~ +55°F	
Key Cold white UGR No	Nominal Voltage (V)	220 - 240 V AC	
UGR No	Type of LED	СОВ	
	Кеу	Cold white	
Outdoor Liso	UGR	No	
	Outdoor Use	lf	





Recommended Use Service life (h) Product variants		Garden 25,000	
Reference	Attributes		
BLP10I-F	Case color : Black (use)		hasta/until/jusqu'à