



LED panel slim 120X60cm - PHILIPS Driver - 72W - UGR19

The PHILIPS recessed LED panel features an elegant, ultra-slim design and cutting-edge technology that provides powerful, uniform lighting in three shades: warm white (3000K), neutral white (4000K), and cool white (6000K). It is a high-efficiency luminaire with a power of 72W and a luminous efficacy of 90lm/w. It incorporates a micro-prismatic diffuser that ensures glare-free lighting ($UGR \leq 19$), ideal for offices, conference rooms, schools, or hospitals. Thanks to its high color rendering index ($CRI > 80$), it reproduces colors very similarly to natural light. The panel can be mounted in false ceilings or directly flush-mounted to drywall using a recessed frame (not included).



Product data

Light temperature	3000°K (use), 4000°K (use), 6000K (use)
Opening angle (°)	160
Certs	CE, ROHS
Energy efficiency class	A+ (2021)
CRI	80-85
LED Panel Dimensions	120x60
Driver	Philips
Efficiency (Lm/w)	90
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Assembly	Recessed
Orientable	No
Power (W)	72
Temperature range	-18°F ~ +55°F
Sensor	No
Nominal Voltage (V)	220 - 240 V AC
Type of LED	SMD 4014
Key	Warm white, Cold white, Neutral white
UGR	UGR19



Outdoor Use	No
Recommended Use	Hotels, Offices, Commerce, Parking
Service life (h)	25,000
Lumens (Lm)	6480

Product variants

Reference	Attributes	
B5234-BF	Light temperature : 6000K (use)	
B5234-BN	Light temperature : 4000°K (use)	