




Recessed circular LED downlight - 6W - Cutout Ø110mm - 5 year warranty

Downlight LED circular empotrable de 6W, diámetro exterior Ø116mm y corte Ø110mm, con marco blanco. Ofrece 450 lúmenes, driver externo sin flicker y filtro EMC para evitar interferencias. Disponible en blanco cálido, blanco neutro y blanco frío. ** 5 años de garantía **



Product data

Light temperature	3000°K, 4000°K, 6500K
Beam angle (°)	120
Certs	CE, ROHS
Energy efficiency class	A+ (2021)
CRI	80-85
Dimensions (mm) LxWxH	Ø116x15
Cutting dimensions (mm)	Ø110
Dimmable	No
Efficiency (Lm/w)	75
Power factor (cosφ)	0.5
Form	Circular, Ultrafine
Frequency of Use	normal
Warranty	5 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	450

Material	Aluminum
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	No
Temperature range	-20°F ~ +40°F
Sensor	No
Nominal Voltage (V)	230V AC
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white
Outdoor Use	No
Service life (h)	25,000

Product variants

Reference

Attributes

B1070-BC

Light temperature : 3000°K



B1070-BF

Light temperature : 6500K



B1070-BN

Light temperature : 4000°K

