









Flexible LED neon 24V DC - 4x10mm - 5 meters - Complete kit - IP67 - 11W/m - Lateral curvature

Flexible LED Neon for decorative lighting with great visual impact. It adapts to various surfaces, offering enormous versatility to bring any design to life. Thanks to its high density of LED chips (120 chips/m), it ensures stable and uniform lighting, with a power of 11W/m. Due to its high level of protection, IP67, this product is suitable for outdoor use. It emits light from one of its side faces, allowing for the lateral curvature. **The complete kit includes 20 staples + 4 plugs (2 initial and 2 final)**



Product data

Light temperature (use) 1800°K (use), 2700°K (use), 30	100°K (use), 4000°K (use), 6000K (use), Blue (to use), Green (to use), Red (to use)
Certs	CE, ROHS
Dimensions (mm) LxWxH	4x10x5000
Cut distance (mm)	50
Guarantee	According to legal warranty: 3 years
IP	IP67
Kelvin (K)	3000, 4000, 6000, 2700, 1800
Material	Silicone
# Chips per meter	120
Power/m (W/m)	11
Nominal Voltage (V)	24V DC
Type of LED	SMD 2835
Key	Warmwhite, Coldwhite, Neutralwhite, Extrawarmwhite, Blue, Red, Green
Outdoor Use	If





Product variants		
Reference	Attributes	
N410-5M-180	Light temperature (use): 1800°K (use)	SING SING SING SING SING SING SING SING
N410-5M-270	Light temperature (use): 2700°K (use)	\$6 ∰ ∰ 100 100 100 100 100 100 10
14+10-5141-270	Light temperature (use), 2700 K (use)	<u> </u>
N410-5M-AZ	Light temperature (use): Blue (to use)	□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □
N410-5M-BC	Light temperature (use): 3000°K (use)	187 (a) (b) (b) (b)
N410-5M-BF	Light temperature (use): 6000K (use)	150 (C) (C) (C) (C) (C) (C) (C) (C)
N410-5M-BN	Light temperature (use): 4000°K (use)	SIO ⊕ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □
N410-5M-RO	Light temperature (use): Red (to use)	10 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
N410-5M-VE	Light temperature (use): Green (to use)	100 PM