









Flexible LED neon 24V DC - 4x10mm - 5 meters - Complete kit - IP67 - 11W/m - Lateral curvature

Flexible LED Neon for decorative lighting with great visual impact. It adapts to various surfaces, offering enormous versatility to bring any design to life. Thanks to its high density of LED chips (120 chips/m), it ensures stable and uniform lighting, with a power of 11W/m. Due to its high level of protection, IP67, this product is suitable for outdoor use. It emits light from one of its side faces, allowing for the lateral curvature. **The complete kit includes 20 staples + 4 plugs (2 initial and 2 final)**



Product data

Light temperature	1800°K, 2700°K, 3000°K, 4000°K, 6000K, Blue, Green, Red ()	
Certs	CE, ROHS	
Dimensions (mm) Lx	WxH 4x10x5000	
Cut distance (mm)	50	
Guarantee	According to legal warranty: 3 years	
IP	IP67	
Kelvin (K)	3000, 4000, 6000, 2700, 1800	
Material	Silicone	
# Chips per meter	120	
Power/m (W/m)	11	
Nominal Voltage (V)	24V DC	
Type of LED	SMD 2835	
Key Warm white, Cold white, Neutral white, Extra warm white, Blue, Red, Green		
Outdoor Use If		





Product variants

Reference

Attributes



Reference	Attributes	
		Is to the control of
N410-5M-180	Light temperature : 1800°K	
N410-5M-270	Light temperature : 2700°K	1509 1509 1509 1009 10097
N410-5M-AZ	Light temperature : Blue	LOW GO CONTROL OF THE PROPERTY
N410-5M-BC	Light temperature : 3000°K	59W @ @ \$C_ 11977
N410-5M-BF	Light temperature : 6000K	Sow G G A 1997
N410-5M-BN	Light temperature : 4000°K	Low Grant Control of the Control of



Reference Attributes

N410-5M-RO Light temperature : Red ()

N410-5M-VE Light temperature : Green