

Proyector LED exterior 50W - 95lm/W - IP65 - Negro

Product data

Light temperature (use)	3000°K (use), 4000°K (use), 6000K (use)
Opening angle (°)	120
Certs	CE, ROHS
Energy efficiency class	F
CRI	80-85
Dimensions (mm) LxWxH	230 x148 x 35
Dimmable	No
Driver	Internal
Efficiency (Lm/w)	95
Power factor (cosφ)	0.9
Frequency (Hz)	50 - 60
Frequency of Use	normal
Projector Range	Slim Series
Guarantee	According to legal warranty: 3 years
IP	IP65
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	3695 (WW) / 4495 (NW) / 4371 (CW)
Material	Aluminum
Material diffuser	Crystal
Assembly	Surface

Orientable	Yes
Power (W)	50
Temperature range	-20°F to +50°F
Sensor	No
Nominal Voltage (V)	220 - 240 V AC
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white
UGR	No
Outdoor Use	If
Recommended Use	Garden, Parking, Fascias
Service life (h)	25,000

Product variants

Reference	Attributes
B1883-2-BC	Light temperature (use): 3000°K (use)
B1883-2-BF	Light temperature (use): 6000K (use)
B1883-2-BN	Light temperature (use): 4000°K (use)