



Recessed circular LED downlight 24W cut-off Ø275mm

Recessed LED Downlight with a power of 24W. Circular in shape with an outer diameter of Ø295mm, a depth of 30mm, and a cutout diameter of Ø275mm. Made with a circular polycarbonate housing and a white lacquered trim ring. Opal polycarbonate diffuser emitting a uniform light. This type of downlight is ideal for both home and professional use. No flicker or any electromagnetic noise. Excellent combination of efficiency and quality design. 24W 230V 120° IP20

Product data	
Light temperature	3000°K, 4000°K, 6000K
Certs	CE, ROHS
Energy efficiency class	A+ (2021)
CRI	80-85
Dimensions (mm) LxWxH	295x295x30
Cutting dimensions (mm)	Ø275-285
Dimmable	No
Efficiency (Lm/w)	80
Form	Circular, Ultrafine
Frequency of Use	normal
Guarantee	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	2000
Material	Polycarbonate
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	No
Temperature range	-20°F ~ +40°F
Nominal Voltage (V)	230
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white





Outdoor Use No
Service life (h) 25,000

Product variants

Reference Attributes

B1243-B-24W-BC Light temperature : 3000°K

B1243-B-24W-BN

Light temperature : 4000°K