

100lm/W
Alta eficiencia
High efficiency
Haute efficacité



22W



Square recessed LED downlight 22W Cut 190 X 190mm

LED Square Recessed Downlights with a power of 22W. Outer diameter of Ø224mm, depth of 27.5mm, and cut-out diameter of Ø190mm. Slim downlight made with a polycarbonate housing featuring a white trim and an opal polycarbonate diffuser to provide homogeneous and intense light. Perfect downlights for both professional and domestic use. Thanks to the DOB, it is a fixture that emits no noise and has no flicker. Excellent combination of efficiency and quality design. 22W 230V 120 degrees IP20

Product data

Light temperature	3000°K, 4000°K, 6000K
Certs	CE, ROHS
Energy efficiency class	A+ (2021)
CRI	80-85
Dimensions (mm) LxWxH	224x224x27.5
Cutting dimensions (mm)	Ø190-200
Dimmable	No
Efficiency (Lm/w)	100
Form	Cuadrado
Frequency of Use	normal
Warranty	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	2200
Material	Polycarbonate
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	No
Temperature range	-20°F ~ +40°F
Nominal Voltage (V)	230
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white



Outdoor Use	No
Recommended Use	Kitchens
Service life (h)	25,000

Product variants

Reference	Attributes	
B1040-B-22W-BC	Light temperature : 3000°K	 <p>100lm/W Alta eficiencia High efficiency Haute efficacité</p> <p>22W</p>
B1040-B-22W-BF	Light temperature : 6000K	 <p>100lm/W Alta eficiencia High efficiency Haute efficacité</p> <p>22W</p>
B1040-B-22W-BN	Light temperature : 4000°K	 <p>100lm/W Alta eficiencia High efficiency Haute efficacité</p> <p>22W</p>