



Slim recessed LED panel 120X30 cm - Driver Philips - 44W - UGR19 - With mounting KIT

The PHILIPS 44W recessed LED panel with driver features a sleek, ultra-slim design and advanced technology that allows it to provide powerful, uniform lighting in 3 shades: warm white (2800K), neutral white (4000K), and cool white (6000K). It incorporates a micro-prismatic diffuser that ensures glare-free lighting (UGR<19), ideal for offices, conference rooms, schools, or hospitals. Thanks to its high color rendering index (CRI>80), it reproduces colors very similarly to natural light. Includes recessed installation kit, with all the accessories for a simple and quick assembly.



Product data

Light temperature	3000°K, 4000°K, 6000K
Certs	CE, ROHS
Energy efficiency class	A+ (2021)
CRI	80-85
LED Panel Dimensions	120x30
Dimmable	Optional, replacing the driver
Driver	Philips
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Assembly	Recessed
Orientable	No
Power (W)	44
Sensor	No
Nominal Voltage (V)	220 - 240 V AC
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white
UGR	UGR19
Outdoor Use	No
Service life (h)	25,000

Driver Philips 123x43mm
9,5 mm



Product variants

Reference

Attributes

B4297-BC

Light temperature : 3000°K



B4297-BF

Light temperature : 6000K



B4297-BN

Light temperature : 4000°K

