



Pack of 10 LED panels slim 60X60 cm - Driver Philips - 44W - UGR19

PACK \times 10 recessed LED panels 60X60 cm - Philips Driver. Elegant and ultra-thin panels with advanced technology for powerful and uniform lighting in three shades of white (3000K, 4000K, 6000K). They have a power of 44W and a luminous flux of 3800 lumens. Ideal for offices, conference rooms, schools, or hospitals. High color rendering index (CRI>80) for accurate color reproduction and low glare index (UGR \le 19). They can be mounted on false ceilings or embedded in plasterboard with a recessed frame (not included).



Product data

Light temperature	Cold White (DO NOT USE), Warm White, Neutral White
Certs	CE, ROHS
Energy efficiency class	A+ (2021)
CRI	80-85
Dimensions (mm) LxWxF	600x600x6mm
LED Panel Dimensions	60x60
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	3800
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	No
Power (W)	44
Sensor	No
Nominal Voltage (V)	220 - 240 V AC
Key	Warm white, Cold white, Neutral white
Outdoor Use	No
Service life (h)	25,000

- Driver Philips 123x43mm





Product variants

Reference Attributes



K5235-BC-10 Light temperature : Warm White



K5235-BF-10 Light temperature : Cold White (DO NOT USE)



K5235-BN-10 Light temperature : Neutral White