



Pack of 6 slim LED panels 60X60 cm - Driver Philips - 44W - UGR19

PACK x 6 recessed LED panels 60X60 cm - Philips Driver. Elegant and ultra-thin panels with advanced technology for powerful and uniform lighting in three shades of white (3000K, 4000K, 6000K). They have a power of 44W and a luminous flux of 3800 lumens. Ideal for offices, conference rooms, schools, or hospitals. High color rendering index (CRI>80) for accurate color reproduction and low glare index (UGR≤19). They can be mounted on false ceilings or recessed in drywall with a mounting frame (not included).




Product data

Light temperature Cold White (DO NOT USE) , Warm White (DO NOT USE) , Neutral White (DO NOT USE)

Certs	CE, ROHS
Energy efficiency class	A+ (2021)
CRI	80-85
LED Panel Dimensions	60x60
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Assembly	Recessed
Orientable	No
Sensor	No
Key	Warm white, Cold white, Neutral white
Outdoor Use	No
Service life (h)	25,000

⇔ Driver Philips 123x43mm



Product variants

Reference	Attributes	
K5235-BC-6	Light temperature : Warm White (DO NOT USE)	
K5235-BF-6	Light temperature : Cold White (DO NOT USE)	
K5235-BN-6	Light temperature : Neutral White (DO NOT USE)	