



Pack of 6 slim LED panels 60X60 cm - Driver Philips - 44W - UGR19

PACK \times 6 recessed LED panels 60X60 cm - Philips Driver. Elegant and ultra-thin panels with advanced technology for powerful and uniform lighting in three shades of white (3000K, 4000K, 6000K). They have a power of 44W and a luminous flux of 3800 lumens. Ideal for offices, conference rooms, schools, or hospitals. High color rendering index (CRI>80) for accurate color reproduction and low glare index (UGR \le 19). They can be mounted on false ceilings or recessed in drywall with a mounting frame (not included).



Product data

| Light temperature | $\operatorname{Cold}\nolimits \operatorname{White}\nolimits \operatorname{,Warm}\nolimits \operatorname{White}\nolimits \operatorname{,Neutral}\nolimits \operatorname{White}\nolimits$ |
|-------------------------|---|
| Certs | CE, ROHS |
| Energy efficiency class | A+ (2021) |
| CRI | 80-85 |
| LED Panel Dimensions | 60x60 |
| Frequency (Hz) | 50 - 60 |
| Frequency of Use | Intensive |
| Guarantee | 3 years |
| IP | IP20 |
| Kelvin (K) | 3000, 4000, 6000 |
| Assembly | Recessed |
| Orientable | No |
| Sensor | No |
| Key | Warm white, Cold white, Neutral white |
| Outdoor Use | No |
| Service life (h) | 25,000 |

- Driver Philips 123x43mm





Reference Attributes K5235-BC-6 Light temperature: Warm White K5235-BF-6 Light temperature: Cold White

Light temperature : Neutral White

K5235-BN-6