




## Linear LED adjustable luminaire for magnetic rail 48V - 6W - UGR16 - White

Linear spotlight for magnetic track with 6W power, featuring a modern design and great versatility. It is easily installed by pressing the base onto the rail, without the need for tools. Its low glare index (UGR16) guarantees high visual comfort for users. In addition, its high color reproduction index (CR1>90) allows colors to be displayed with high fidelity. With a rotation angle of 180°, it allows directing the light to the desired point. Available in black and in two shades: warm white and neutral white.



## **Product data**

Housing color	White (use), Black (use)	
Light temperature	2700°K (use), 4000°K (use)	
Certs	CE, ROHS	
CRI	90-95	
Dimensions (mm) LxWxH	112x58x23	
Guarantee	According to legal warranty: 3 years	
IP	IP20	
Kelvin (K)	4000, 2800	
Lumens (Lm)	530, 1350	
Material	Aluminum	
Orientable	Yes	
Power (W)	6	
Nominal Voltage (V)	48V	
Track Type	Magnetic	
Key	Warm white, Neutral white	
UGR	UGR16	
Service life (h)	25,000	
Dimmable	No	
Sensor	No	
Outdoor Use	No	
Recommended Use	Hotels, Kitchens, Commerce, Museums - Galleries	





Product variants		
Reference	Attributes	Ć 6W UGR16
PML-6WU18-B-BC	Housing color: White (use), Light temperature : 2700°K (use)	Ú 6W UGR16
PML-6WU18-B-BN	Housing color: White (use), Light temperature : 4000°K (use)	Ċ ew Dunte
PML-6WU18-N-BC	Housing color: Black (use), Light temperature : 2700°K (use)	Ú 6W UGR16
PML-6WU18-N-BN	Housing color: Black (use), Light temperature : 4000°K (use)	