



## Pack of 4 slim LED panels 120X60cm - PHILIPS Driver - 72W - UGR19

PACK of 4 recessed LED panels 120x60cm - PHILIPS driver. The panels feature a sleek, ultra-slim design and cutting-edge technology that allows them to provide powerful, uniform lighting in 3 shades: warm white (3000K), neutral white (4000K), and cool white (6000K). They are high-efficiency fixtures with a power of 72W and a luminous flux of 5900 lumens. They incorporate a micro-prismatic diffuser that ensures glare-free lighting (UGR≤19), ideal for offices, conference rooms, schools, or hospitals. Thanks to their high color rendering index (CRI>80), they reproduce colors very similarly to natural light. The panels can be mounted on false ceilings or recessed directly into drywall using a recessed frame (not included).



## **Product data**

Agent etting in term partier to Opening angle (°)160CertsCE, ROHSEnergy efficiency classA+ (2021)CRI80-85Dimensions (mm) LxWxH1195 x 595 x 7LED Panel Dimensions120x60DriverPhilipsFrequency (Hz)50 - 60Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014KeyWarm white, Cold white, Neutral white	Light temperature	Cold White , Warm White , Neutral White
CertsCE, ROHSEnergy efficiency classA+ (2021)CRI80-85Dimensions (mm) LxWxH1195 x 595 x 7LED Panel Dimensions120x60DriverPhilipsFrequency (Hz)50 - 60Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014		
Energy efficiency class A+ (2021)   CRI 80-85   Dimensions (mm) LxWxH 1195 × 595 × 7   LED Panel Dimensions 120x60   Driver Philips   Frequency (Hz) 50 - 60   Frequency of Use Intensive   Guarantee According to legal warranty: 3 years   IP IP20   Kelvin (K) 3000, 4000, 6000   Lumens (Lm) 5900   Assembly Recessed   Orientable No   Power (W) 72   Temperature range -18°F ~ +55°F   Sensor No   Nominal Voltage (V) 220 - 240 V AC   Type of LED SMD 4014		CE, ROHS
CRI 80-85   Dimensions (mm) LxWxH 1195 x 595 x 7   LED Panel Dimensions 120x60   Driver Philips   Frequency (Hz) 50 - 60   Frequency of Use Intensive   Guarantee According to legal warranty: 3 years   IP IP20   Kelvin (K) 3000, 4000, 6000   Lumens (Lm) 5900   Assembly Recessed   Orientable No   Power (W) 72   Temperature range -18°F ~+55°F   Sensor No   Nominal Voltage (V) 220 - 240 V AC   Type of LED SMD 4014	Energy efficiency class	
LED Panel Dimensions120x60DriverPhilipsFrequency (Hz)50 - 60Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014		80-85
DriverPhilipsFrequency (Hz)50 - 60Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014	Dimensions (mm) LxWxH	1195 x 595 x 7
Frequency (Hz)50 - 60Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014	LED Panel Dimensions	120x60
Frequency of UseIntensiveGuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014	Driver	Philips
GuaranteeAccording to legal warranty: 3 yearsIPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014	Frequency (Hz)	50 - 60
IPIP20Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014	Frequency of Use	Intensive
Kelvin (K)3000, 4000, 6000Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014	Guarantee	According to legal warranty: 3 years
Lumens (Lm)5900AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014	IP	IP20
AssemblyRecessedOrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014	Kelvin (K)	3000, 4000, 6000
OrientableNoPower (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014	Lumens (Lm)	5900
Power (W)72Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014	Assembly	Recessed
Temperature range-18°F ~ +55°FSensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014	Orientable	No
SensorNoNominal Voltage (V)220 - 240 V ACType of LEDSMD 4014	Power (W)	72
Nominal Voltage (V)220 - 240 V ACType of LEDSMD 4014	Temperature range	-18°F ~ +55°F
Type of LED SMD 4014	Sensor	No
	Nominal Voltage (V)	220 - 240 V AC
Key Warm white, Cold white, Neutral white	Type of LED	SMD 4014
	Кеу	Warm white, Cold white, Neutral white





UGR Outdoor Use Recommended Use Service life (h)	UGR19 No Hotels, Offices, Commerce, Parking 25,000	
Product variants		
Reference K5234-BF-4	Attributes Light temperature : Cold White	
K5234 BN 4	Light tomporature : Neutral White	

K5234-BN-4

Light temperature : Neutral White