

Pack of 2 LED panels slim 120X30 cm - Driver Philips - 44W - UGR19

PACK x 2 Recessed LED Panels 120X30 cm - Philips Driver Elegant and ultra-thin panels with advanced technology for powerful and even lighting in three shades of white (3000K, 4000K, 6000K). They have a power of 44W and a luminous flux of 2900 lumens. Ideal for offices, conference rooms, schools, or hospitals. High Color Rendering Index (CRI>80) for accurate color reproduction and low glare index (UGR≤19). They can be mounted on false ceilings or recessed in drywall with an embedded frame (not included).

⇌ Driver Philips 123x43mm




Product data

Light temperature	Cold White (DO NOT USE) , Warm White , Neutral White
Certs	CE, ROHS
CRI	80-85
Dimensions (mm) LxWxH	1200x300x6mm
Cutting dimensions (mm)	1200x300mm
LED Panel Dimensions	120x30
Dimmable	Optional, replacing the driver
Driver	External
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	3 years
IP	IP65
Kelvin (K)	3000, 4000, 6000
Material diffuser	Polycarbonate
Assembly	Recessed
Power (W)	44
Sensor	No
Nominal Voltage (V)	230
Type of LED	SMD 2835
Key	Cold white, Neutral white, Extra warm white
Outdoor Use	No
Service life (h)	25,000

⇌ Driver Philips 123x43mm



Product variants

Reference	Attributes	
K5236-2-BC	Light temperature : Warm White	
K5236-2-BF	Light temperature : Cold White (DO NOT USE)	
K5236-2-BN	Light temperature : Neutral White	