



Pack of 2 LED panels slim 120X30 cm - Driver Philips - 44W - UGR19

PACK x 2 Recessed LED Panels 120X30 cm - Philips Driver Elegant and ultra-thin panels with advanced technology for powerful and even lighting in three shades of white (3000K, 4000K, 6000K). They have a power of 44W and a luminous flux of 2900 lumens. Ideal for offices, conference rooms, schools, or hospitals. High Color Rendering Index (CRI>80) for accurate color reproduction and low glare index (UGR≤19). They can be mounted on false ceilings or recessed in drywall with an embedded frame (not included).

⇐ Driver Philips 123x43mm



Product data

Light temperatureCold White (DO NOT USE) , Warm White (DO NOT USE) , Neutral White (DO NOT USE)

CertsCE, ROHS

CRI80-85

Dimensions (mm) LxWxH1200x300x6mm

Cutting dimensions (mm)1200x300mm

LED Panel Dimensions120x30

DimmableOptional, replacing the driver

DriverExternal

Frequency (Hz)50 - 60

Frequency of UseIntensive

Guarantee3 years

IPIP65

Kelvin (K)3000, 4000, 6000

Material diffuserPolycarbonate

AssemblyRecessed

Power (W)44

SensorNo

Nominal Voltage (V)230

Type of LEDSMD 2835

KeyCold white, Neutral white, Extra warm white

Outdoor UseNo

Service life (h)25,000

⇐ Driver Philips 123x43mm



Product variants

Reference	Attributes	
K5236-2-BC	Light temperature : Warm White (DO NOT USE)	
K5236-2-BF	Light temperature : Cold White (DO NOT USE)	
K5236-2-BN	Light temperature : Neutral White (DO NOT USE)	