


PACK DE
4



Pack of 4 slim LED panels 120X30 cm - Driver Philips - 44W - UGR19

PACK x 4 Recessed LED Panels 120X30 cm - Philips Driver Elegant and ultra-thin panels with advanced technology for powerful and uniform lighting in three shades of white (3000K, 4000K, 6000K). They have a power of 44W and a luminous flux of 2900 lumens. Ideal for offices, conference rooms, schools, or hospitals. High color rendering index (CRI>80) for accurate color reproduction and low glare index (UGR≤19). They can be mounted on false ceilings or built into drywall with a recessed frame (not included).



Product data

Light temperature	Cold White , Warm White , Neutral White
Certs	CE, ROHS
CRI	80-85
Dimensions (mm) LxWxH	1200x300x6mm
Cutting dimensions (mm)	1200x300mm
LED Panel Dimensions	120x30
Dimmable	Optional, replacing the driver
Driver	External
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Warranty	3 years
IP	IP65
Kelvin (K)	3000, 4000, 6000
Material diffuser	Polycarbonate
Assembly	Recessed
Power (W)	44
Sensor	No
Nominal Voltage (V)	230
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white
Outdoor Use	No
Service life (h)	25,000

➡ Driver Philips 123x43mm



Product variants

Reference

Attributes

K5236-4-BC

Light temperature : Warm White



K5236-4-BF

Light temperature : Cold White



K5236-4-BN

Light temperature : Neutral White

