



Recessed LED Panel - 120X30cm - TRIAC dimmable - 44W - UGR19

The 120×30 cm recessed LED panel features an ultra-slim design and cutting-edge technology that allows it to provide powerful and even lighting. Highly efficient, it has a power of 44W and a light output of 2900 lumens. It incorporates a TRIAC regulation driver, which provides the capability to adjust the light intensity. Thanks to its low glare index, UGR19, this panel provides great visual comfort. Available in three shades: warm white (3000K), neutral white (4000K), and cool white (6000K).



Product data

Light temperatureCold White (DO NOT USE), Warm WI	hite (DO NOT USE), Neutral White (DO NOT USE)
Certs	CE, ROHS
CRI	80-85
Dimensions (mm) LxWxH	1200 x 300 x 6
Cutting dimensions (mm)	1200x300
LED Panel Dimensions	120x30
Dimmable	Yes
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	2900
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	No
Power (W)	44
Sensor	No
Nominal Voltage (V)	220 - 240 V AC
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white
UGR	UGR19
Outdoor Use	No
Service life (h)	25,000





Product variants		
Reference	Attributes	
K5236-TRIAC-BC	Light temperature : Warm White (DO NOT USE)	
K5236-TRIAC-BF	Light temperature : Cold White (DO NOT USE)	
K5236-TRIAC-BN	Light temperature : Neutral White (DO NOT USE)	

Light temperature : Neutral White (DO NOT USE)

K5236-TRIAC-BN