





## Recessed LED Panel - 120X30cm - PUSH Dimmable - 44W - UGR19

The  $120 \times 30$  cm recessed LED panel features a sleek and ultra-slim design along with cutting-edge technology that allows it to provide powerful and uniform lighting. It is a high-efficiency luminaire with a power of 44W and a luminous flux of 3980 lumens. It includes a PUSH dimming driver, which offers the possibility to adjust the light intensity. Thanks to its low glare index, UGR19, this panel provides great visual comfort. It is available in three tones: warm white (3000K), neutral white (4000K), and cool white (6000K).



## **Product data**

| Light temperature       | ${\sf ColdWhite,WarmWhite,NeutralWhite}$ |
|-------------------------|--|
| Certs                   | CE, ROHS                                 |
| CRI                     | 80-85                                    |
| Cutting dimensions (mm) | 1200x300                                 |
| LED Panel Dimensions    | 120x30                                   |
| Dimmable                | Yes                                      |
| Frequency (Hz)          | 50 - 60                                  |
| Frequency of Use        | Intensive                                |
| Guarantee               | According to legal warranty: 3 years     |
| IP                      | IP20                                     |
| Kelvin (K)              | 3000, 4000, 6000                         |
| Lumens (Lm)             | 2900                                     |
| Material diffuser       | Polycarbonate                            |
| Assembly                | Recessed                                 |
| Orientable              | No                                       |
| Power (W)               | 44                                       |
| Nominal Voltage (V)     | 220 - 240 V AC                           |
| Type of LED             | SMD 2835                                 |
| Key                     | Warm white, Cold white, Neutral white    |
| Outdoor Use             | No                                       |
| Service life (h)        | 25,000                                   |





## **Product variants**

Reference

Attributes

K5236-PUSH-BC

Light temperature : Warm White



K5236-PUSH-BF

Light temperature: Cold White



K5236-PUSH-BN

Light temperature : Neutral White

