



Recessed LED Panel - 120X30cm - PUSH Dimmable - 44W - UGR19

The 120 x 30 cm recessed LED panel features a sleek and ultra-slim design along with cutting-edge technology that allows it to provide powerful and uniform lighting. It is a high-efficiency luminaire with a power of 44W and a luminous flux of 3980 lumens. It includes a PUSH dimming driver, which offers the possibility to adjust the light intensity. Thanks to its low glare index, UGR19, this panel provides great visual comfort. It is available in three tones: warm white (3000K), neutral white (4000K), and cool white (6000K).



Product data

Light temperature Cold White (DO NOT USE) , Warm White (DO NOT USE) , Neutral White (DO NOT USE)

Certs	CE, ROHS
CRI	80-85
Cutting dimensions (mm)	1200x300
LED Panel Dimensions	120x30
Dimmable	Yes
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	2900
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	No
Power (W)	44
Nominal Voltage (V)	220 - 240 V AC
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white
Outdoor Use	No
Service life (h)	25,000



Product variants

Reference	Attributes	
K5236-PUSH-BC	Light temperature : Warm White (DO NOT USE)	
K5236-PUSH-BF	Light temperature : Cold White (DO NOT USE)	
K5236-PUSH-BN	Light temperature : Neutral White (DO NOT USE)	