







Recessed LED Panel 120X60cm - TRIAC Dimmable - 72W - UGR19

The 120×60 cm recessed LED panel features an ultra-slim design and cutting-edge technology that allows it to provide powerful and uniform lighting. Highly efficient, it has a power of 72W and a luminous flux of 5900 lumens. It incorporates two TRIAC control drivers, which allows for the adjustment of light intensity. Thanks to its low glare index, UGR19, this panel provides great visual comfort. Available in three shades: warm white (3000K), neutral white (4000K), and cool white (6000K).



Product data

Light temperature	${\sf ColdWhite,WarmWhite,NeutralWhite}$
Beam angle (°)	120
Certs	CE, ROHS
CRI	80-85
Dimensions (mm) LxWxH	1200 x 600 x 6
Cutting dimensions (mm)	1200x600
LED Panel Dimensions	120x60
Dimmable	Yes
Efficiency (Lm/w)	85
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Warranty	According to legal warranty: 3 years
Warranty IP	According to legal warranty: 3 years
	<u> </u>
IP	IP20
IP Kelvin (K)	IP20 3000, 4000, 6000
IP Kelvin (K) Lumens (Lm)	IP20 3000, 4000, 6000 5900
IP Kelvin (K) Lumens (Lm) Material diffuser	IP20 3000, 4000, 6000 5900 Polycarbonate
IP Kelvin (K) Lumens (Lm) Material diffuser Assembly	IP20 3000, 4000, 6000 5900 Polycarbonate Recessed
IP Kelvin (K) Lumens (Lm) Material diffuser Assembly Orientable	IP20 3000, 4000, 6000 5900 Polycarbonate Recessed No
IP Kelvin (K) Lumens (Lm) Material diffuser Assembly Orientable Power (W)	IP20 3000, 4000, 6000 5900 Polycarbonate Recessed No





Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white
UGR	UGR19
Outdoor Use	No
Service life (h)	25,000

Product variants

Reference Attributes





K5234-TRIAC-BN Light temperature : Neutral White



