



## Recessed LED Panel 120X60cm - TRIAC Dimmable - 72W - UGR19

The 120 x 60 cm recessed LED panel features an ultra-slim design and cutting-edge technology that allows it to provide powerful and uniform lighting. Highly efficient, it has a power of 72W and a luminous flux of 5900 lumens. It incorporates two TRIAC control drivers, which allows for the adjustment of light intensity. Thanks to its low glare index, UGR19, this panel provides great visual comfort. Available in three shades: warm white (3000K), neutral white (4000K), and cool white (6000K).



## Product data

| Light temperature       | Cold White , Warm White , Neutral White |
|-------------------------|---|
| Opening angle (°)       | 120                                     |
| Certs                   | CE, ROHS                                |
| CRI                     | 80-85                                   |
| Dimensions (mm) LxWxH   | 1200 x 600 x 6                          |
| Cutting dimensions (mm) | 1200x600                                |
| LED Panel Dimensions    | 120x60                                  |
| Dimmable                | Yes                                     |
| Efficiency (Lm/w)       | 85                                      |
| Frequency (Hz)          | 50 - 60                                 |
| Frequency of Use        | Intensive                               |
| Guarantee               | According to legal warranty: 3 years    |
| IP                      | IP20                                    |
| Kelvin (K)              | 3000, 4000, 6000                        |
| Lumens (Lm)             | 5900                                    |
| Material diffuser       | Polycarbonate                           |
| Assembly                | Recessed                                |
| Orientable              | No                                      |
| Power (W)               | 72                                      |
| Temperature range       | -18°F ~ +55°F                           |
| Sensor                  | No                                      |
| Nominal Voltage (V)     | 220 - 240 V AC                          |
|                         |   |





| Type of LED      |                                   | SMD 2835        |  |
|------------------|-----------------------------------|-----------------|--|
| Кеу              | Warm white, Cold white            | , Neutral white |  |
| UGR              |                                   | UGR19           |  |
| Outdoor Use      |                                   | No              |  |
| Service life (h) |                                   | 25,000          |  |
| Product variants |                                   |                 |  |
| Reference        | Attributes                        |                 |  |
| K5234-TRIAC-BC   | Light temperature : Warm White    |                 |  |
| K5234-TRIAC-BF   | Light temperature : Cold White    |                 |  |
| K5234-TRIAC-BN   | Light temperature : Neutral White |                 |  |