



Recessed LED panel - 120X60cm - 0-10V dimmable - 72W - UGR19

The 120 x 60 cm recessed LED panel features an ultra-slim design and cutting-edge technology that provides powerful and uniform lighting. With high efficiency, it has a power of 72W and a luminous flux of 5900 lumens. It incorporates two 0-10V regulation drivers, which provides the possibility of adjusting the light intensity. Thanks to its low glare index, UGR19, this panel provides great visual comfort. Available in three shades: warm white (3000K), neutral white (4000K), and cool white (6000K).



Product data

Light temperature Cold White (DO NOT USE) , Warm White (DO NOT USE) , Neutral White (DO NOT USE)

Opening angle (°)	120
Certs	CE, ROHS
CRI	80-85
Dimensions (mm) LxWxH	1200 x 600 x 6
Cutting dimensions (mm)	1200x600
LED Panel Dimensions	120x60
Dimmable	Yes
Efficiency (Lm/w)	85
Frequency (Hz)	50 - 60
Frequency of Use	Intensive
Guarantee	According to legal warranty: 3 years
IP	IP20
Kelvin (K)	3000, 4000, 6000
Lumens (Lm)	5900
Material diffuser	Polycarbonate
Assembly	Recessed
Orientable	No
Power (W)	72
Temperature range	-18°F ~ +55°F
Sensor	No
Nominal Voltage (V)	220 - 240 V AC
Type of LED	SMD 2835
Key	Warm white, Cold white, Neutral white
UGR	UGR19
Outdoor Use	No
Service life (h)	25,000



Product variants

Reference	Attributes	
K5234-0-10-BC	Light temperature : Warm White (DO NOT USE)	
K5234-0-10-BF	Light temperature : Cold White (DO NOT USE)	
K5234-0-10-BN	Light temperature : Neutral White (DO NOT USE)	