



Recessed LED panel - 120X60cm - 0-10V dimmable - 72W - UGR19

The 120 x 60 cm recessed LED panel features an ultra-slim design and cutting-edge technology that provides powerful and uniform lighting. With high efficiency, it has a power of 72W and a luminous flux of 5900 lumens. It incorporates two 0-10V regulation drivers, which provides the possibility of adjusting the light intensity. Thanks to its low glare index, UGR19, this panel provides great visual comfort. Available in three shades: warm white (3000K), neutral white (4000K), and cool white (6000K).



Product data

| | |
|-------------------------|---|
| Light temperature | Cold White , Warm White , Neutral White |
| Beam angle (°) | 120 |
| Certs | CE, ROHS |
| CRI | 80-85 |
| Dimensions (mm) LxWxH | 1200 x 600 x 6 |
| Cutting dimensions (mm) | 1200x600 |
| LED Panel Dimensions | 120x60 |
| Dimmable | Yes |
| Efficiency (Lm/w) | 85 |
| Frequency (Hz) | 50 - 60 |
| Frequency of Use | Intensive |
| Warranty | According to legal warranty: 3 years |
| IP | IP20 |
| Kelvin (K) | 3000, 4000, 6000 |
| Lumens (Lm) | 5900 |
| Material diffuser | Polycarbonate |
| Assembly | Recessed |
| Orientable | No |
| Power (W) | 72 |
| Temperature range | -18°F ~ +55°F |
| Sensor | No |
| Nominal Voltage (V) | 220 - 240 V AC |



| | |
|------------------|---------------------------------------|
| Type of LED | SMD 2835 |
| Key | Warm white, Cold white, Neutral white |
| UGR | UGR19 |
| Outdoor Use | No |
| Service life (h) | 25,000 |

Product variants

| Reference | Attributes | |
|---------------|-----------------------------------|---|
| K5234-0-10-BC | Light temperature : Warm White |  |
| K5234-0-10-BF | Light temperature : Cold White |  |
| K5234-0-10-BN | Light temperature : Neutral White |  |