

Recessed LED Panel - 120X60cm - DALI dimmable - 72W - UGR19

The 120 x 60 cm recessed LED panel features an ultra-thin design and cutting-edge technology that allows it to provide powerful and uniform lighting. Highly efficient, it has a power of 72W and a luminous flux of 5900 lumens. It incorporates two DALI regulation drivers, which provides the possibility to adjust the light intensity. Thanks to its low glare index, UGR19, this panel provides great visual comfort. Available in three shades: warm white (3000K), neutral white (4000K), and cool white (6000K).




Product data

Light temperature Cold White (DO NOT USE) , Warm White (DO NOT USE) , Neutral White (DO NOT USE)

| | |
|-------------------------|---------------------------------------|
| Opening angle (°) | 120 |
| Certs | CE, ROHS |
| CRI | 80-85 |
| Dimensions (mm) LxWxH | 1200 X 600 X 6 |
| Cutting dimensions (mm) | 1200x600 |
| LED Panel Dimensions | 120x60 |
| Dimmable | Yes |
| Efficiency (Lm/w) | 85 |
| Frequency (Hz) | 50 - 60 |
| Frequency of Use | Intensive |
| Guarantee | According to legal warranty: 3 years |
| IP | IP20 |
| Kelvin (K) | 3000, 4000, 6000 |
| Lumens (Lm) | 5900 |
| Material diffuser | Polycarbonate |
| Assembly | Recessed |
| Orientable | No |
| Power (W) | 72 |
| Temperature range | -18°F ~ +55°F |
| Sensor | No |
| Nominal Voltage (V) | 220 - 240 V AC |
| Type of LED | SMD 2835 |
| Key | Warm white, Cold white, Neutral white |
| UGR | UGR19 |
| Outdoor Use | No |
| Service life (h) | 25,000 |



Product variants

| Reference | Attributes | |
|---------------|--|---|
| K5234-DALI-BC | Light temperature : Warm White (DO NOT USE) |  |
| K5234-DALI-BF | Light temperature : Cold White (DO NOT USE) |  |
| K5234-DALI-BN | Light temperature : Neutral White (DO NOT USE) |  |