




LOT DE
10
ORIENTABLE



KIT x 10 - Tilting downlight ring silver color Ø90mm + Bulb GU10 5W + Socket GU10

10 complete kits for GU10 bulb installation. Each kit includes: 1. GU10 LED Dichroic Bulb of 5W available in 4 shades: Extra warm white: 2700K - 450 lm Warm white: 3000K - 475 lm Neutral white: 4000K - 500 lm Cool white: 6000K - 525 lm 2. Adjustable polycarbonate downlight in black color 3. Ceramic socket for GU10 bulb. Includes pre-wiring.



Product data

Housing color	White, Black, Gray
Light temperature	2700°K, 3000°K, 4000°K, 6000K
Beam angle (°)	120
Cap	GU10
Certs	CE, ROHS
CRI	80-85
Dimensions (mm) LxWxH	Bulb: Ø50x55
Cutting dimensions (mm)	Ø75
Form	Circular
Warranty	According to legal warranty: 3 years
Kelvin (K)	3000, 4000, 6000, 2700
Kit	Yes
Lumens (Lm)	450, 500, 475, 525
Material	Polycarbonate
Power (W)	5
Nominal Voltage (V)	220 - 240 V AC
Key	Warm white, Cold white, Neutral white



Product variants

Reference

Attributes

Reference	Attributes	
		
K981-R-B-270-10	Housing color: White, Light temperature : 2700°K	
		
K981-R-B-BC-10	Housing color: White, Light temperature : 3000°K	
		
K981-R-B-BF-10	Housing color: White, Light temperature : 6000K	
		
K981-R-B-BN-10	Housing color: White, Light temperature : 4000°K	
		
K981-R-G-10-BC	Housing color: Gray, Light temperature : 3000°K	
		
K981-R-G-10-BF	Housing color: Gray, Light temperature : 6000K	

Reference	Attributes	
		
K981-R-G-270-10	Housing color: Gray, Light temperature : 2700°K	
K981-R-G-BN-10	Housing color: Gray, Light temperature : 4000°K	
K981-R-N-270-10	Housing color: Black, Light temperature : 2700°K	
K981-R-N-BC-10	Housing color: Black, Light temperature : 3000°K	
K981-R-N-BF-10	Housing color: Black, Light temperature : 6000K	
K981-R-N-BN-10	Housing color: Black, Light temperature : 4000°K	