




Recessed/trimless linear LED spotlight for plasterboard - 12W - UGR18 - CRI90 - White

Recessed LED spotlight, integrable into drywall, with a power of 12W. Provides an aesthetic finish, with no visible edges or flanges. Includes Osram LED chips and KeGu driver. It stands out for its low glare index (UGR<18) and its high color rendering index (CRI>90). Available in black and warm white tones (2700K) and neutral white (4000K). **
5-Year Warranty **



Product data

Light temperature Certs	2700°K, 4000°K	
Certs		
	CE, ROHS	
Energy efficiency class	F	
CRI	90-95	
Dimensions (mm) LxWxH	145 X 91 X 49	
Cutting dimensions (mm)	145 times 41	
Dimmable	No	
Driver	External, KeGu	
Form	Linear	
Warranty	5 years	
IP	IP20	
Kelvin (K)	4000, 2700	
Lumens (Lm) war	m white: 715lm - neutral white: 921lm	
Material	Aluminum	
Material diffuser	Polycarbonate	
Assembly	Integration	
Orientable	No	
Power (W)	12	
Sensor	No	
Nominal Voltage (V)	220 - 240 V AC	
Type of LED	OSRAM Chip	
Key	Cold white, Extra warm white	
UGR	UGR18	
Outdoor Use	No	
$Recommended \ Use Dining \ room, Bedrooms, Hotels, Kitchens, Commerce, Living \ room, Museums-Galleries, Fashion \ and \ retail, Furniture$		
Service life (h)	25,000	





Product variants		
Reference	Attributes	
B1219-12W-B-270	Housing color: White, Light temperature : 2700°K	
B1219-12W-B-BN	Housing color: White, Light temperature : 4000°K	•
B1219-12W-N-270	Housing color: Black, Light temperature : 2700°K	
		À
B1219-12W-N-BN	Housing color: Black, Light temperature : 4000°K	