





Recessed/Trimless linear LED spotlight for plasterboard - 20W - UGR18 - CRI90 - White

Recessed LED spotlight, integrable in drywall, with a power of 20W. Provides an aesthetic finish, without noticeable edges or flanges. Incorporates Osram LED chips and KeGu driver. It stands out for its low glare index (UGR<18) and its high color rendering index (CRI>90). Available in black and warm white shades (2700K) and neutral white (4000K). ** 5-Year Warranty **



Product data

Housing color	White, Black
Light temperature	2700°K, 4000°K
Certs	CE, ROHS
Energy efficiency class	F
CRI	90-95
Dimensions (mm) LxWxH	274 x 79 x 49
Cutting dimensions (mm)	277 x 41
Dimmable	No
Driver	External, KeGu
Form	Linear
Guarantee	5 years
IP	IP20
Kelvin (K)	4000, 2700
Lumens (Lm)	warm white: 1260lm - neutral white: 1728lm
Assembly	Integration
Orientable	No
Power (W)	20
Sensor	No
Nominal Voltage (V)	220 - 240 V AC
Type of LED	OSRAM Chip
Key	Neutral white, Extra warm white
UGR	UGR18
Outdoor Use	No
Recommended Use	Dining room, Bedrooms, Hotels, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retail
Service life (h)	25,000



Product variants

Reference	Attributes	
B1219-20W-B-270	Housing color: White, Light temperature : 2700°K	
B1219-20W-B-BN	Housing color: White, Light temperature : 4000°K	
B1219-20W-N-270	Housing color: Black, Light temperature : 2700°K	
B1219-20W-N-BN	Housing color: Black, Light temperature : 4000°K	