




Recessed/Trimless linear LED spotlight for plasterboard - 20W - UGR18 - CRI90 - White

Recessed LED spotlight, integrable in drywall, with a power of 20W. Provides an aesthetic finish, without noticeable edges or flanges. Incorporates Osram LED chips and KeGu driver. It stands out for its low glare index (UGR<18) and its high color rendering index (CRI>90). Available in black and warm white shades (2700K) and neutral white (4000K).** 5-Year Warranty **



Product data

Housing color	White (use), Black (use)	
Light temperature	2700°K (use), 4000°K (use)	
Certs	CE, ROHS	
Energy efficiency class	F	
CRI	90-95	
Dimensions (mm) LxWxH	274 x 79 x 49	
Cutting dimensions (mm)	277 x 41	
Dimmable	No	
Driver	External, KeGu	
Form	Linear	
Guarantee	5 years	
IP	IP20	
Kelvin (K)	4000, 2700	
Lumens (Lm)	warm white: 1260lm - neutral white: 1728lm	
Assembly	Integration	
Orientable	No	
Power (W)	20	
Sensor	No	
Nominal Voltage (V)	220 - 240 V AC	
Type of LED	OSRAM Chip	
Key	Neutral white, Extra warm white	
UGR	UGR18	
Outdoor Use	No	
$\underline{ \text{Recommended UseDining room, Bedrooms, Hotels, Kitchens, Commerce, Living room, Museums-Galleries, Fashion and retail} \\$		
Service life (h) 25,000		





Product variants		
Reference	Attributes	
B1219-20W-B-270	Housing color: White (use), Light temperature: 2700°K (use)	
B1219-20W-B-BN	Housing color: White (use), Light temperature : 4000°K (use)	7
B1219-20W-N-270	Housing color: Black (use), Light temperature : 2700°K (use)	
		<u></u>
B1219-20W-N-BN	Housing color: Black (use), Light temperature: 4000°K (use)	