


Recessed triple LED downlight - 6W - UGR18 - CRI90 - OSRAM Chip - Black

White recessed LED linear luminaire composed of three 6W power lights in total. Incorporates Osram LED chips and KeGu driver. Available in neutral white (4000K) and extra warm white (2700K). It stands out for its low glare rating (UGR<18) and its high color rendering index (CRI>90), providing great visual comfort while allowing colors to be displayed with high fidelity, similar to natural light. ** 5-Year Warranty **



Product data

Light temperature 2700°K, 4000°K Certs CE, ROHS Energy efficiency class G CRI 90-95 Dimensions (mm) LXWXH 147x 45 x49, 105 x45 x49 Cutting dimensions (mm) LXWXH 97 times 37 Dimmable 8 Driver External, Ked Form Linear Warranty 5 years IP 1920 Kelvin (K) 4000, 2700 Limens (Lm) neutral white 470lm - warm white 420lm Material Aluminum Material diffuser Polycarbonate Sesembly Recessed Power (W) 6 Sensor No Somial Voltage (V) 220-240 VA Key Neutral white, Extra warm white UGR UGR18 Key Neutral white, Extra warm white UGR UGR18 Keonmended Use Dining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retail Seam angle (*) 25,000 Geam angle (*) 25,000	Housing color	White, Black
Energy efficiency class G CRI 90-95 Dimensions (mm) LxWxH 147x 45x 49, 105 x 45 x 49 Cutting dimensions (mm) 97 times 37 Dimmable No Driver External, KeGu Form Linear Warranty 5 years IP IP20 Kelvin (K) 4000, 2700 Lumens (Lm) neutral white 470lm- warm white 420lm Material Aluminum Material diffuser Polycarbonate Assembly Recessed Power (W) 6 Sensor No Nominal Voltage (V) 220 - 240 V AC Type of LED OSRAM Chip Key Neutral white, Extra warm white UGR UGR18 Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retail Service life (h) 25,000 Beam angle (*) 45 Grientable 6	Light temperature	2700°K, 4000°K
CRI 90-95 Dimensions (mm) LxWxH 147 x 45 x 49, 105 x 45 x 49 Cutting dimensions (mm) 97 times 37 Dimmable No Driver External, KeGu Form Linear Warranty 5 years IP IP20 Kelvin (K) 4000, 2700 Lumens (Lm) neutral white 470lm-warm white 420lm Material Aluminum Material difffuser Polycarbonate Assembly Recessed Power (W) 6 Sensor No Nominal Voltage (V) 20 - 240 V AC Type of LED OSRAM Chip Key Neutral white, Extra warm white UGR UGR18 Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retail Service life (h) 25,000 Beam angle (*) 45 Orientable No	Certs	CE, ROHS
Dimensions (mm) LxWxH 147x 45x 49, 105x 45x 49 Cutting dimensions (mm) 97 times 37 Dimmable No Driver External, KeGu Form Linear Warranty 5 years IP IP20 Kelvin (K) 4000, 270 Lumens (Lm) neutral white 470lm - warm white 420lm Material Aluminum Material diffuser Polycarbonate Assembly Recessed Power (W) 6 Sensor No Nominal Voltage (V) 220 - 240 V AC Type of LED OSRAM Chip Key Neutral white, Extra warm white UGR UGR18 Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retail Service life (h) 25,000 Beam angle (*) 45 Orientable No	Energy efficiency class	G
Cutting dimensions (mm) 97 times 37 Dimmable No Driver External, KeGu Form Linear Warranty 5 years IP IP20 Kelvin (K) 4000, 2700 Lumens (Lm) neutral white 470lm - warm white 420lm Material Aluminum Material diffuser Polycarbonate Assembly Recessed Power (W) 6 Sensor No Nominal Voltage (V) 220 - 240 V AC Type of LED OSRAM Chip Key Neutral white, Extra warm white UGR UGR18 Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retail Service life (h) 25,000 Beam angle (°) 45 Grientable No	CRI	90-95
Dimmable No Driver External, KeGu Form Linear Warranty 5 years IP IP20 Kelvin (K) 4000, 2700 Lumens (Lm) neutral white 470Im - warm white 420Im Material Aluminum Material diffuser Polycarbonate Assembly Recessed Power (W) 6 Sensor No Nominal Voltage (V) 220 - 240 V AC Type of LED OSRAM Chip Key Neutral white, Extra warm white UGR UGR18 Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retail Service life (h) 25,000 Beam angle (°) 45 Orientable No	Dimensions (mm) LxWxH	147 x 45 x 49, 105 x 45 x 49
Driver External, KeGu Form Linear Warranty 5 years IP IP20 Kelvin (K) 4000, 2700 Lumens (Lm) neutral white 470lm - warm white 420lm Material Aluminum Material diffuser Polycarbonate Assembly Recessed Power (W) 6 Sensor No Nominal Voltage (V) 220 - 240 V AC Type of LED OSRAM Chip Key Neutral white, Extra warm white UGR UGR18 Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retail Service life (h) 25,000 Beam angle (°) 45 Orientable No	Cutting dimensions (mm)	97 times 37
FormLinearWarranty5 yearsIPIP20Kelvin (K)4000, 2700Lumens (Lm)neutral white 470Im - warm white 420ImMaterialAluminumMaterial diffuserPolycarbonateAssemblyRecessedPower (W)6SensorNoNominal Voltage (V)220 - 240 V ACType of LEDOSRAM ChipKeyNeutral white, Extra warm whiteUGRUGR 18Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retailService life (h)25,000Beam angle (°)45OrientableNo	Dimmable	No
Warranty5 yearsIPIP20Kelvin (K)4000, 2700Lumens (Lm)neutral white 470Im - warm white 420ImMaterialAluminumMaterial diffuserPolycarbonateAssemblyRecessedPower (W)6SensorNoNominal Voltage (V)220 - 240 V ACType of LEDOSRAM ChipKeyNeutral white, Extra warm whiteUGRUGR18Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retailService life (h)25,000Beam angle (°)45OrientableNo	Driver	External, KeGu
IPIP20Kelvin (K)4000, 2700Lumens (Lm)neutral white 470lm-warm white 420lmMaterialAluminumMaterial diffuserPolycarbonateAssemblyRecessedPower (W)6SensorNoNominal Voltage (V)220 - 240 V ACType of LEDOSRAM ChipKeyNeutral white, Extra warm whiteUGRUGR18Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retailService life (h)25,000Beam angle (°)45OrientableNo	Form	Linear
Kelvin (K)4000, 2700Lumens (Lm)neutral white 470lm - warm white 420lmMaterialAluminumMaterial diffuserPolycarbonateAssemblyRecessedPower (W)6SensorNoNominal Voltage (V)220 - 240 V ACType of LEDOSRAM ChipKeyNeutral white, Extra warm whiteUGRUGR18Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retailService life (h)25,000Beam angle (°)45OrientableNo	Warranty	5 years
Lumens (Lm)neutral white 470lm - warm white 420lmMaterialAluminumMaterial diffuserPolycarbonateAssemblyRecessedPower (W)6SensorNoNominal Voltage (V)220 - 240 V ACType of LEDOSRAM ChipKeyNeutral white, Extra warm whiteUGRUGR18Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retailService life (h)25,000Beam angle (°)45OrientableNo	IP	IP20
MaterialAluminumMaterial diffuserPolycarbonateAssemblyRecessedPower (W)6SensorNoNominal Voltage (V)220 - 240 V ACType of LEDOSRAM ChipKeyNeutral white, Extra warm whiteUGRUGR18Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retailService life (h)25,000Beam angle (°)45OrientableNo	Kelvin (K)	4000, 2700
Material diffuserPolycarbonateAssemblyRecessedPower (W)6SensorNoNominal Voltage (V)220 - 240 V ACType of LEDOSRAM ChipKeyNeutral white, Extra warm whiteUGRUGR18Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retailService life (h)25,000Beam angle (°)45OrientableNo	Lumens (Lm)	neutral white 470lm - warm white 420lm
AssemblyRecessedPower (W)6SensorNoNominal Voltage (V)220 - 240 V ACType of LEDOSRAM ChipKeyNeutral white, Extra warm whiteUGRUGR18Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retailService life (h)25,000Beam angle (°)45OrientableNo	Material	Aluminum
Power (W) 6 Sensor No Nominal Voltage (V) 220 - 240 V AC Type of LED OSRAM Chip Key Neutral white, Extra warm white UGR Neutral white, Extra warm white UGR UGR18 Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retail Service life (h) 25,000 Beam angle (°) 45 Orientable	Material diffuser	Polycarbonate
SensorNoNominal Voltage (V)220 - 240 V ACType of LEDOSRAM ChipKeyNeutral white, Extra warm whiteUGRUGR18Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retailService life (h)25,000Beam angle (°)45OrientableNo	Assembly	Recessed
Nominal Voltage (V)220 - 240 V ACType of LEDOSRAM ChipKeyNeutral white, Extra warm whiteUGRUGR18Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retailService life (h)25,000Beam angle (°)45OrientableNo	Power (W)	6
Type of LED Key Neutral white, Extra warm white UGR Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retail Service life (h) 25,000 Beam angle (°) Orientable	Sensor	No
KeyNeutral white, Extra warm whiteUGRUGR18Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retailService life (h)25,000Beam angle (°)45OrientableNo	Nominal Voltage (V)	220 - 240 V AC
UGR 18 Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retail Service life (h) 25,000 Beam angle (°) 45 Orientable No	Type of LED	OSRAM Chip
Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, Commerce, Living room, Museums - Galleries, Fashion and retail Service life (h) Beam angle (°) Orientable No	Key	Neutral white, Extra warm white
Service life (h) 25,000 Beam angle (°) 45 Orientable No	UGR	UGR18
Beam angle (°) 45 Orientable No	Recommended UseDining room, Bedrooms, Hotels, Offices, Kitchens, C	Commerce, Living room, Museums - Galleries, Fashion and retail
Orientable No	Service life (h)	25,000
	Beam angle (°)	45
Outdoor Use No	Orientable	No
	Outdoor Use	No





Product variants Reference Attributes B1218-6W-B-270 Housing color: White, Light temperature : 2700°K B1218-6W-B-BN Housing color: White, Light temperature : 4000°K B1218-6W-N-270 Housing color: Black Light temperature : 2700°K

Housing color: Black, Light temperature : 4000°K

B1218-6W-N-BN